

MWX65

All-in-One Wall panel

AUDAC

► Features

- Audio source selection
- Volume control
- Line level input (RCA)
- Microphone level input (XLR)
- Local mixing
- 15V Phantom power
- 2.5" Graphical Display
- 2-Band tone control

► Applications

- Residential buildings
- Industrial buildings
- Commercial buildings
- Conference rooms
- Offices, Hotels
- Restaurants, Bars



The MWX65 is an All-in-One Wall panel controller to be used in combination with the AUDAC MTX series Multi-Zone audio matrix systems.

It can control the input signal and volume for one zone and also contains an additional line and microphone level input which can be patched to the zone its connected to.

Both input selection and volume control as well as two band tone control can be controlled using the versatile rotatable push-dial, while the integrated 2.5" graphical display ensures a user friendly experience.

An XLR connector is provided as additional microphone input, while the line input is performed using RCA connectors. The signals applied to these inputs can be used as one additional local input. This enables you to connect any CD or MP3 player as local music source or connect a microphone for speeches or other announcements. The input mixing can be done by using both push-lock potentiometers.

The microphone input has the possibility to provide 15V Phantom power which can be turned on and off by software configuration.

The wiring between the matrix and the wall panel should be performed by using standard UTP CAT5 Cabling, which transfers both the control and audio signals to the matrix while providing the power supply for the wall panel.

► Specifications

| SYSTEM SPECIFICATIONS | | |
|---|---|-----------------------------------|
| Digital control | RS485 | |
| Audio transfer | Analogue differential (Dual mono) | |
| Inputs | Line level (RCA) Microphone level (Female XLR) | |
| Phantom power | 15 V DC (software enabling) | |
| Microphone Sensitivity | -50 dB ~ -15 dB | |
| Microphone THD+N | < 0.1% | |
| Line Sensitivity | -12 dB ~ +12 dB | |
| Line THD+N | < 0.05% | |
| Cabling | UTP CAT 5 (Up to 300 meter) | |
| Display | 2.5" Graphical Full colour | |
| PRODUCT FEATURES | | |
| Dimensions (Width x Height x Depth) | 153 x 94 x 45 mm | |
| Built-in Depth | 37 mm | |
| Weight net | 0.21 Kg | |
| Construction | ABS | |
| Connector | 8-pin Euro-Terminal Block | |
| Colour | White (RAL9010) | MWX65/W |
| | Black (RAL9005) | MWX65/B |
| SHIPPING & ORDERING | | |
| Packaging | Carton box | |
| Shipping weight and volume | 0.34 Kg ~ 0.00225 Cbm | |
| Accessories | Flush mount Installation boxes | WB5065/FS: Concrete & Brick walls |
| | Surface mount Installation boxes | WB5065/FG: Wooden & Gypsum walls |
| | | WB5065/SW: White version |
| | | WB5065/SB: Black version |
| *AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our products | | |