HZA4-70



The HZA4-70 is a four-channel amplifier with direct 100 V line (high impedance) outputs. It's equipped with Ecler's proprietary SPM 100 Technology - Channel N, which allows for 100 V speaker lines connection without using 100 V line transformers, as this kind of amplifiers usually do. This fact has many advantages, being the main ones the audio quality improvement (specially in the low-end frequencies) and the convection cooling, 100% silent.

Key features

- 4 mono balanced inputs
- 4 70 W amplified outputs (100V line level)
- 4 volume remote control ports (0 10 VDC)
- Euroblock connectors
- SPM 100 amplification Technology Channel N (no 100 V output transformers used):
 - Improved frequency response (specially at the low-end)
 - Convection cooling (100% silent and increased reliability)
 - Great efficiency
- Low weight
- Auto stand-by function after 2 minutes without audio input signals, with instantaneous auto-recovery
- Thermal protection
- Overload protection
- Anti-clip system



Tech. Characte	ristics	HZAH-70	SP OVL CUP	TH SP OVL CLP TH HZA4-70	59
Power at bandpass 1% TH	D: 1 Channel @ 100V	74 WRMS @ 136Ω	Remote control:	DC	0-10V/
	4 Channels @ 100V	64 WRMS @ 136Ω		No attenuation	OV
Frequency response (-3dB)		30Hz - 50kHz		Full attenuation	+10V
High pass filter 3rd order Butterworth		70Hz		Connectors	Termina
THD + Noise @ 1kHz Full power		<0.05%	Auto power:	Threshold	>-30dB
Signal Noise Ratio @ 100V		>90dB		Time	100 se
Channel Crosstalk @ 1kHz/100V		>90dB	Mains voltage	Depending on your country.	
Inputs:	Sensitivity nom/Impedance	OdBV/>20k©		See characteristics in the back of the unit.	
	Connectors	Terminal block (Symmetrical)	Power consumption:	pink noise, 1/8 power @ 136©	298VA
Outputs:	Connectors	Terminal block		pink noise, 1/3 power @ 136©	407VA
Indicators:	Power	Green (ON), Red (Standby)		Standby	<3W
	Signal present	-35dB	Dimensions:	Panel	482.6x
	Clip			Depth (Handle excluded)	373mm
	Overload		Weight		10.25k
	Thermal				

Applications

• Multi-zone BGM and paging systems with 100V line speakers, combined with the MIM054 and MIM088 matrixes and SAM series preamplifiers

Suggested 100V line speakers:

• AUDEO series

/O.1A max

nal block

ec. aprox

x88mm

- IC / IW / ICPLUS series
- AMBIT SERIES
- ECL106 series

Suggested remote control accessories:

• WP series wall panels



Applus⁶

ISO 9001

All product characteristics are subject to variation due to production tolerances. ECLER, S.A. reserves the right to make changes or improvements in the design or manufacturing that may affect these product specifications. Motors, 166-168 08038 Barcelona - Spain - Domestic sales / Ventas España (+34) 902221400 Export sales / Ventas Export (+34) 902331400 General calls (+34) 932238403 Fax (+34) 932238404