



Picture Perfect Projection



Bright projection - 2500 ANSI Lumens

O de

XGA resolution, 3500:1 contrast ratio for sharp, detailed presentations and graphics

Low ownership costs - up to 6000hrs lamp life

 \bigcirc

Energy saving <1W standby mode



RS232 for meeting room control systems



Quick start up and shut down time



Remote control



Lightweight and portable



Optoma DX211 filter-free design – virtually no maintenance



Perfect for use with interactive whiteboards at school, delivering an important presentation at work, or watching a movie on the big screen at home, the Optoma DX211 is the perfect projector for all your display needs.

Bright, crystal clear, vibrant projection delivers captivating presentations and beautiful graphics to leave your audience speechless every time the DX211 is turned on.

Hassle-free, long lasting projection with the 6000 hour lamp-life, filter-free low maintenance design combined with our unique Optoma Colour and Imager guarantees.

CLEAR, FOCUSED IMAGES

DarkChip3™ technology from Texas Instruments produces a stunning 3500:1 contrast ratio for pin sharp, crystal clear images. Crisper whites and ultra rich blacks bring the image to life



1000:1 contrast ratio

3500:1 contrast ratio

‡Simulated Image

AMAZING COLOURS

The DX211 incorporates BrilliantColor™ technology to produce stunningly bright images with perfectly balanced life-like colours. Preset display modes allow you to achieve a perfect image every time.

COLOUR AND IMAGER GUARANTEE

Bright colours and fantastic image quality are guaranteed for an amazing 5 years after purchase - giving piece of mind that the technology inside the Optoma DX211 projector won't fade or degrade.







VIRTUALLY MAINTENANCE FREE

The DX211 provides lower cost of ownership, longer life and improved reliability. The filter-free projector design does not require regular filter cleaning or filter replacement, saving you time and money.





ENVIRONMENTALLY FRIENDLY

The DX211 incorporates energy saving features to conserve power and extend the lamp life:



To achieve the maximum 6000hrs² lamp life time the projector should be operating in ECO mode and the shut down timer should be enabled to automatically switch off the projector if it is accidentally left on when no longer required. Enabling the <1W Standby mode will ensure the minimum energy consumption when the projector is not being used.



It takes less than 10 seconds for the projector to power up and shutdown, saving both time and energy.

SMOOTH, SEAMLESS PROJECTION

Even in the fastest moving scenes, the DX211 will project a smooth and seamless image. The rapid response of DLP® technology ensures that the projected movie or video game remains perfect and precise.





With

Without

CONTROL

The extensive RS232 command set makes it simple and easy to control the DX211 with any control system.



AMX Compatibility – Dynamic Discovery Protocol is incorporated into the DX211. This feature allows for easy installation with AMX control systems.

FEATURES

- 6 preset display modes including Movie mode
- 4:3 and 16:9 widescreen
- Classroom mode 1500 ANSI Lumens
- Password protection for added security
- Ceiling mount the projector or project from a coffee table
- Easy to use remote with direct source control



Enjoy big bright pictures in the office, classroom day or night



We know that improving our products is the best way to reduce our impact on the environment. That's why at Optoma, we design our products to have a long usable life, use fewer materials, ship with the minimum packaging and be free of all possible toxic substances. Naturally, energy efficiency and being recyclable are built in at the design stage. With each new product, we strive towards minimising our environmental impact. For full details of Optoma Project Green please visit our website.

DX211 SPECIFICATIONS

Display Technology	Native Resolution	XGA 1024 x 768					
Brightness 2500 ANSI Lumens	Display Technology	0.55" XGA DLP® chip, Technology by Texas Instruments					
Contrast Ratio 3500:1 Lamp Life² 6000/5000 hours (ECO/BRIGHT mode) Noise Level 28dB (ECO mode) Weight / Dimensions (W x D x H) 2.3 kg / 286 x 192 x 84mm INPUTS 15 Pin D-Sub VGA, SCART via adaptor, Component via adaptor S-Video 4 Pin Mini Din Composite RCA Jack Component via adaptor OUTPUT 15 Pin D-Sub Control RS232 3 Pin mini-DIN Aspect Ratio 4:3 Native, 16:9 compatible On Screen Display 17 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish, Greek, Norwegian/Danish, Hungarian, Czech, Turkish and Arabic Video Compatibility PAL SECAM 625/576ip, NTSC 525/480ip HD 720p/1080i/p HD 720p/1080i/p Uniformity 85% Zoom 1.1x Manual Zoom Projection Distance 1.2 − 12m Image Size 0.70 − 7.70m (27.49" − 303.12") Diagonal 4:3 Keystone ±40° Vertical Operating Conditions Operating 5 − 35° C, 80% Humidity (Max), 3000m Altitude (Max) Power Supply 100 − 240V, 50 − 60Hz Power Consumption 233W BRIGHT mode < 1W Standby mode,	Compatible Resolutions	UXGA, SXGA+, SXGA, WXGA, XGA, SVGA					
Lamp Life2	Brightness ¹	2500 ANSI Lumens					
Noise Level Weight / Dimensions (W x D x H) 15 Pin D-Sub VGA, SCART via adaptor, Component via adaptor S-Video 4 Pin Mini Din Composite RCA Jack OUTPUT 15 Pin D-Sub Control RS232 3 Pin mini-DIN Aspect Ratio 4:3 Native, 16:9 compatible On Screen Display 17 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish, Greek, Norwegian/Danish, Hungarian, Czech, Turkish and Arabic Video Compatibility PAL SECAM 625/576i\p, NTSC 525/480i\p HD 720p/1080i/p Uniformity 85% Zoom 1.1x Manual Zoom Projection Distance 1.2 - 12m Image Size 0.70 - 7.70m (27.49" - 303.12") Diagonal 4:3 Keystone 240° Vertical Operating Conditions Operating Power Supply 100 - 240V, 50 - 60Hz Power Consumption 233W BRIGHT mode < 1W Standby mode, 207W ECO mode < 1W Standby mode. Security Kensington Lock Port, Password Protection In the BOX Power Cord, VGA Cable, UM CD, Quick Start Guide, Remote, Batteries RoHS Compliant Lamp Warranty Warranty Warranty will vary by country. Please see: www.optomaeurope.com or ask your local supplier for details Colour Guarantee³ 5 Years	Contrast Ratio	3500:1					
Weight / Dimensions (W x D x H) INPUTS 15 Pin D-Sub VGA, SCART via adaptor, Component via adaptor S-Video 4 Pin Mini Din Composite RCA Jack OUTPUT 15 Pin D-Sub Control RS232 3 Pin mini-DIN Aspect Ratio 4:3 Native, 16:9 compatible On Screen Display 17 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish, Greek, Norwegian/Danish, Hungarian, Czech, Turkish and Arabic Video Compatibility PAL SECAM 625/576i\(\nabla\), NTSC 525/480i\(\nabla\)p HD 720p/1080i/p Uniformity 85% Zoom 1.1x Manual Zoom Projection Distance 1.2 - 12m Image Size 0.70 - 7.70m (27.49" - 303.12") Diagonal 4:3 Keystone ±40° Vertical Operating Conditions Operating 5 - 35° C, 80% Humidity (Max), 3000m Altitude (Max) Power Supply 100 - 240V, 50 - 60Hz Power Consumption 233W BRIGHT mode < 1W Standby mode, 207W ECO mode < 1W Standby mode. Security Kensington Lock Port, Password Protection In the BOX Power Cord, VGA Cable, UM CD, Quick Start Guide, Remote, Batteries RoHS Compliant Lamp Warranty Warranty Warranty will vary by country. Please see: www.optomaeurope.com or ask your local supplier for details Colour Guarantee³ 5 Years	Lamp Life ²	6000/5000 hours (ECO/BRIGHT mode)					
INPUTS 15 Pin D-Sub VGA, SCART via adaptor, Component via adaptor S-Video 4 Pin Mini Din Composite RCA Jack OUTPUT 15 Pin D-Sub Control RS232 3 Pin mini-DIN Aspect Ratio 4:3 Native, 16:9 compatible On Screen Display 17 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish, Greek, Norwegian/Danish, Hungarian, Czech, Turkish and Arabic Video Compatibility PAL SECAM 625/576i\p, NTSC 525/480i\p HD 720p/1080i/p Uniformity 85% Zoom 1.1x Manual Zoom Projection Distance 1.2 – 12m Image Size 0.70 – 7.70m (27.49" – 303.12") Diagonal 4:3 Keystone ±40° Vertical Operating Conditions Operating 5 - 35° C, 80% Humidity (Max), 3000m Altitude (Max) Power Supply 100 – 240V, 50 – 60Hz Power Consumption 233W BRIGHT mode < 1W Standby mode, 207W ECO mode < 1W Standby mode. Security Kensington Lock Port, Password Protection In the BOX Power Cord, VGA Cable, UM CD, Quick Start Guide, Remote, Batteries RoHS Compliant Lamp Warranty Warranty will vary by country. Please see: www.optomaeurope.com or ask your local supplier for details Colour Guarantee³ 5 Years	Noise Level	28dB (ECO mode)					
Component via adaptor S-Video 4 Pin Mini Din Composite RCA Jack OUTPUT 15 Pin D-Sub Control RS232 3 Pin mini-DIN Aspect Ratio 4:3 Native, 16:9 compatible On Screen Display 17 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish, Greek, Norwegian/Danish, Hungarian, Czech, Turkish and Arabic Video Compatibility PAL SECAM 625/576\\(\frac{1}{2}\), NTSC 525/480\\(\frac{1}{2}\) HD 720p/1080i/p Uniformity 85% Zoom 1.1x Manual Zoom Projection Distance 1.2 - 12m Image Size 0.70 - 7.70m (27.49" - 303.12") Diagonal 4:3 Keystone ±40° Vertical Operating Conditions Operating 5 - 35° C, 80% Humidity (Max), 3000m Altitude (Max) Power Supply 100 - 240V, 50 - 60Hz Power Consumption 233W BRIGHT mode < 1W Standby mode, 207W EC0 mode < 1W Standby mode. Security Kensington Lock Port, Password Protection In the BOX Power Cord, VGA Cable, UM CD, Quick Start Guide, Remote, Batteries RoHS Compliant Lamp Warranty Warranty will vary by country. Please see: www.optomaeurope.com or ask your local supplier for details Colour Guarantee³ 5 Years	Weight / Dimensions (W x D x H)	2.3 kg / 286 x 192 x 84mm					
S-Video 4 Pin Mini Din Composite RCA Jack OUTPUT 15 Pin D-Sub Control RS232 3 Pin mini-DIN Aspect Ratio 4:3 Native, 16:9 compatible On Screen Display 17 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish, Greek, Norwegian/Danish, Hungarian, Czech, Turkish and Arabic Video Compatibility PAL SECAM 625/576\p, NTSC 525/480\p HD 720p/1080i/p Uniformity 85% Zoom 1.1x Manual Zoom Projection Distance 1.2 - 12m Image Size 0.70 - 7.70m (27.49" - 303.12") Diagonal 4:3 Keystone ±40° Vertical Operating Conditions Operating 5 - 35° C, 80% Humidity (Max), 3000m Altitude (Max) Power Supply 100 - 240V, 50 - 60Hz Power Consumption 233W BRIGHT mode < 1W Standby mode, 207W ECO mode < 1W Standby mode. Security Kensington Lock Port, Password Protection In the BOX Power Cord, VGA Cable, UM CD, Quick Start Guide, Remote, Batteries RoHS Compliant Lamp Warranty Warranty will vary by country. Please see: www.optomaeurope.com or ask your local supplier for details Colour Guarantee³ 5 Years	INPUTS	15 Pin D-Sub VGA, SCART via adaptor,					
Composite RCA Jack OUTPUT 15 Pin D-Sub Control RS232 3 Pin mini-DIN Aspect Ratio 4:3 Native, 16:9 compatible On Screen Display 17 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish, Greek, Norwegian/Danish, Hungarian, Czech, Turkish and Arabic Video Compatibility PAL SECAM 625/576i\p, NTSC 525/480i\p HD 720p/1080i/p Uniformity 85% Zoom 1.1x Manual Zoom Projection Distance 1.2 – 12m Image Size 0.70 – 7.70m (27.49" – 303.12") Diagonal 4:3 Keystone ±40° Vertical Operating Conditions Operating 5 - 35° C, 80% Humidity (Max), 3000m Altitude (Max) Power Supply 100 – 240V, 50 – 60Hz Power Consumption 233W BRIGHT mode < 1W Standby mode, 207W ECO mode < 1W Standby mode. Security Kensington Lock Port, Password Protection In the BOX Power Cord, VGA Cable, UM CD, Quick Start Guide, Remote, Batteries RoHS Compliant Lamp Warranty Warranty will vary by country. Please see: www.optomaeurope.com or ask your local supplier for details Colour Guarantee³ 5 Years		Component via adaptor					
OUTPUT 15 Pin D-Sub Control RS232 3 Pin mini-DIN Aspect Ratio 4:3 Native, 16:9 compatible On Screen Display 17 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish, Greek, Norwegian/Danish, Hungarian, Czech, Turkish and Arabic Video Compatibility PAL SECAM 625/576i\p, NTSC 525/480i\p HD 720p/1080i/p Uniformity 85% Zoom 1.1x Manual Zoom Projection Distance 1.2 – 12m Image Size 0.70 – 7.70m (27.49" – 303.12") Diagonal 4:3 Keystone ±40° Vertical Operating Conditions Operating 5 - 35° C, 80% Humidity (Max), 3000m Altitude (Max) Power Supply 100 – 240V, 50 – 60Hz Power Consumption 233W BRIGHT mode < 1W Standby mode, 207W ECO mode < 1W Standby mode. Security Kensington Lock Port, Password Protection In the BOX Power Cord, VGA Cable, UM CD, Quick Start Guide, Remote, Batteries ROHS Compliant Lamp Warranty G months or 1000 hours – whichever comes sooner Warranty Warranty will vary by country. Please see: www.optomaeurope.com or ask your local supplier for details Colour Guarantee³ 5 Years		S-Video 4 Pin Mini Din					
Control RS232 3 Pin mini-DIN Aspect Ratio 4:3 Native, 16:9 compatible On Screen Display 17 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish, Greek, Norwegian/Danish, Hungarian, Czech, Turkish and Arabic Video Compatibility PAL SECAM 625/576i\p, NTSC 525/480i\p HD 720p/1080i/p Uniformity 85% Zoom 1.1x Manual Zoom Projection Distance 1.2 – 12m Image Size 0.70 – 7.70m (27.49" – 303.12") Diagonal 4:3 Keystone ±40° Vertical Operating Conditions Operating 5 - 35° C, 80% Humidity (Max), 3000m Altitude (Max) Power Supply 100 – 240V, 50 – 60Hz Power Consumption 233W BRIGHT mode < 1W Standby mode, 207W ECO mode < 1W Standby mode. Security Kensington Lock Port, Password Protection In the BOX Power Cord, VGA Cable, UM CD, Quick Start Guide, Remote, Batteries ROHS Compliant Lamp Warranty G months or 1000 hours – whichever comes sooner Warranty Warranty will vary by country. Please see: www.optomaeurope.com or ask your local supplier for details Colour Guarantee³ 5 Years		Composite RCA Jack					
Aspect Ratio 0n Screen Display 17 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish, Greek, Norwegian/Danish, Hungarian, Czech, Turkish and Arabic Video Compatibility PAL SECAM 625/576i\p, NTSC 525/480i\p HD 720p/1080i/p Uniformity 85% Zoom 1.1x Manual Zoom Projection Distance 1.2 – 12m Image Size 0.70 – 7.70m (27.49" – 303.12") Diagonal 4:3 Keystone ±40° Vertical Operating Conditions Operating 5 - 35° C, 80% Humidity (Max), 3000m Altitude (Max) Power Supply 100 – 240V, 50 – 60Hz Power Consumption 233W BRIGHT mode < 1W Standby mode, 207W ECO mode < 1W Standby mode. Security Kensington Lock Port, Password Protection In the BOX Power Cord, VGA Cable, UM CD, Quick Start Guide, Remote, Batteries RoHS Compliant Lamp Warranty Warranty will vary by country. Please see: www.optomaeurope.com or ask your local supplier for details Colour Guarantee³ 5 Years	OUTPUT	15 Pin D-Sub					
On Screen Display 17 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish, Greek, Norwegian/Danish, Hungarian, Czech, Turkish and Arabic Video Compatibility PAL SECAM 625/576i\p, NTSC 525/480i\p HD 720p/1080i/p Uniformity 85% Zoom 1.1x Manual Zoom Projection Distance 1.2 – 12m Image Size 0.70 – 7.70m (27.49" – 303.12") Diagonal 4:3 Keystone ±40° Vertical Operating Conditions Operating 5 - 35° C, 80% Humidity (Max), 3000m Altitude (Max) Power Supply 100 – 240V, 50 – 60Hz Power Consumption 233W BRIGHT mode < 1W Standby mode, 207W ECO mode < 1W Standby mode. Security Kensington Lock Port, Password Protection In the BOX Power Cord, VGA Cable, UM CD, Quick Start Guide, Remote, Batteries RoHS Compliant Lamp Warranty Warranty will vary by country. Please see: www.optomaeurope.com or ask your local supplier for details Colour Guarantee³ 5 Years	Control	RS232 3 Pin mini-DIN					
Portuguese, Polish, Dutch, Russian, Finnish, Swedish, Greek, Norwegian/Danish, Hungarian, Czech, Turkish and Arabic Video Compatibility PAL SECAM 625/576i\p, NTSC 525/480i\p HD 720p/1080i/p Uniformity 85% Zoom 1.1x Manual Zoom Projection Distance 1.2 – 12m Image Size 0.70 – 7.70m (27.49" – 303.12") Diagonal 4:3 Keystone ±40° Vertical Operating Conditions Operating 5 - 35° C, 80% Humidity (Max), 3000m Altitude (Max) Power Supply 100 – 240V, 50 – 60Hz Power Consumption 233W BRIGHT mode < 1W Standby mode, 207W ECO mode < 1W Standby mode. Security Kensington Lock Port, Password Protection In the BOX Power Cord, VGA Cable, UM CD, Quick Start Guide, Remote, Batteries RoHS Compliant Lamp Warranty Warranty will vary by country. Please see: www.optomaeurope.com or ask your local supplier for details Colour Guarantee³ 5 Years	Aspect Ratio	4:3 Native, 16:9 compatible					
Greek, Norwegian/Danish, Hungarian, Czech, Turkish and Arabic Video Compatibility PAL SECAM 625/576i\p, NTSC 525/480i\p HD 720p/1080i/p Uniformity 85% Zoom 1.1x Manual Zoom Projection Distance 1.2 – 12m Image Size 0.70 – 7.70m (27.49" – 303.12") Diagonal 4:3 Keystone ±40° Vertical Operating Conditions Operating 5 - 35° C, 80% Humidity (Max), 3000m Altitude (Max) Power Supply 100 – 240V, 50 – 60Hz Power Consumption 233W BRIGHT mode < 1W Standby mode, 207W ECO mode < 1W Standby mode. Security Kensington Lock Port, Password Protection In the BOX Power Cord, VGA Cable, UM CD, Quick Start Guide, Remote, Batteries ROHS Compliant Lamp Warranty Warranty will vary by country. Please see: www.optomaeurope.com or ask your local supplier for details Colour Guarantee³ 5 Years	On Screen Display	17 Languages: English, German, French, Italian, Spanish,					
Turkish and Arabic Video Compatibility PAL SECAM 625/576i\p, NTSC 525/480i\p HD 720p/1080i/p Uniformity 85% Zoom 1.1x Manual Zoom Projection Distance 1.2 – 12m Image Size 0.70 – 7.70m (27.49" – 303.12") Diagonal 4:3 Keystone ±40° Vertical Operating Conditions Operating 5 - 35° C, 80% Humidity (Max), 3000m Altitude (Max) Power Supply 100 – 240V, 50 – 60Hz Power Consumption 233W BRIGHT mode < 1W Standby mode, 207W ECO mode < 1W Standby mode. Security Kensington Lock Port, Password Protection In the BOX Power Cord, VGA Cable, UM CD, Quick Start Guide, Remote, Batteries RoHS Compliant Lamp Warranty Warranty will vary by country. Please see: www.optomaeurope.com or ask your local supplier for details Colour Guarantee³ 5 Years		Portuguese, Polish, Dutch, Russian, Finnish, Swedish,					
Video Compatibility PAL SECAM 625/576i\p, NTSC 525/480i\p HD 720p/1080i/p Uniformity 85% Zoom 1.1x Manual Zoom Projection Distance 1.2 – 12m Image Size 0.70 – 7.70m (27.49" – 303.12") Diagonal 4:3 Keystone ±40° Vertical Operating Conditions Operating 5 - 35° C, 80% Humidity (Max), 3000m Altitude (Max) Power Supply 100 – 240V, 50 – 60Hz Power Consumption 233W BRIGHT mode < 1W Standby mode, 207W ECO mode < 1W Standby mode. Security Kensington Lock Port, Password Protection In the BOX Power Cord, VGA Cable, UM CD, Quick Start Guide, Remote, Batteries RoHS Compliant Lamp Warranty G months or 1000 hours – whichever comes sooner Warranty Warranty will vary by country. Please see: www.optomaeurope.com or ask your local supplier for details Colour Guarantee³ 5 Years		Greek, Norwegian/Danish, Hungarian, Czech,					
HD 720p/1080i/p Uniformity 85% Zoom 1.1x Manual Zoom Projection Distance 1.2 – 12m Image Size 0.70 – 7.70m (27.49" – 303.12") Diagonal 4:3 Keystone ±40° Vertical Operating Conditions Operating 5 - 35° C, 80% Humidity (Max), 3000m Altitude (Max) Power Supply 100 – 240V, 50 – 60Hz Power Consumption 233W BRIGHT mode < 1W Standby mode, 207W ECO mode < 1W Standby mode. Security Kensington Lock Port, Password Protection In the BOX Power Cord, VGA Cable, UM CD, Quick Start Guide, Remote, Batteries RoHS Compliant Lamp Warranty 6 months or 1000 hours – whichever comes sooner Warranty Warranty will vary by country. Please see: www.optomaeurope.com or ask your local supplier for details Colour Guarantee³ 5 Years		Turkish and Arabic					
Uniformity 85% Zoom 1.1x Manual Zoom Projection Distance 1.2 – 12m Image Size 0.70 – 7.70m (27.49" – 303.12") Diagonal 4:3 Keystone ±40° Vertical Operating Conditions Operating 5 - 35° C, 80% Humidity (Max), 3000m Altitude (Max) Power Supply 100 – 240V, 50 – 60Hz Power Consumption 233W BRIGHT mode < 1W Standby mode, 207W ECO mode < 1W Standby mode. Security Kensington Lock Port, Password Protection In the BOX Power Cord, VGA Cable, UM CD, Quick Start Guide, Remote, Batteries RoHS Compliant Lamp Warranty 6 months or 1000 hours – whichever comes sooner Warranty Warranty will vary by country. Please see: www.optomaeurope.com or ask your local supplier for details Colour Guarantee³ 5 Years	Video Compatibility	PAL SECAM 625/576i\p, NTSC 525/480i\p					
Zoom		HD 720p/1080i/p					
Projection Distance 1.2 – 12m Image Size 0.70 – 7.70m (27.49" – 303.12") Diagonal 4:3 Keystone ±40° Vertical Operating Conditions Operating 5 - 35° C, 80% Humidity (Max), 3000m Altitude (Max) Power Supply 100 – 240V, 50 – 60Hz Power Consumption 233W BRIGHT mode < 1W Standby mode, 207W ECO mode < 1W Standby mode. Security Kensington Lock Port, Password Protection In the BOX Power Cord, VGA Cable, UM CD, Quick Start Guide, Remote, Batteries RoHS Compliant Lamp Warranty 6 months or 1000 hours – whichever comes sooner Warranty Warranty will vary by country. Please see: www.optomaeurope.com or ask your local supplier for details Colour Guarantee³ 5 Years	Uniformity	85%					
Image Size 0.70 – 7.70m (27.49" – 303.12") Diagonal 4:3 Keystone ±40° Vertical Operating Conditions Operating 5 - 35° C, 80% Humidity (Max), 3000m Altitude (Max) Power Supply 100 – 240V, 50 – 60Hz Power Consumption 233W BRIGHT mode < 1W Standby mode, 207W ECO mode < 1W Standby mode. Security Kensington Lock Port, Password Protection In the BOX Power Cord, VGA Cable, UM CD, Quick Start Guide, Remote, Batteries RoHS Compliant Lamp Warranty 6 months or 1000 hours – whichever comes sooner Warranty Warranty will vary by country. Please see: www.optomaeurope.com or ask your local supplier for details Colour Guarantee³ 5 Years	Zoom	1.1x Manual Zoom					
Keystone ±40° Vertical Operating Conditions Operating 5 - 35° C, 80% Humidity (Max), 3000m Altitude (Max) Power Supply 100 - 240V, 50 - 60Hz Power Consumption 233W BRIGHT mode < 1W Standby mode,	Projection Distance	1.2 – 12m					
Operating Conditions Operating 5 - 35° C, 80% Humidity (Max), 3000m Altitude (Max) Power Supply 100 - 240V, 50 - 60Hz Power Consumption 233W BRIGHT mode < 1W Standby mode, 207W ECO mode < 1W Standby mode. Security Kensington Lock Port, Password Protection In the BOX Power Cord, VGA Cable, UM CD, Quick Start Guide, Remote, Batteries RoHS Compliant Lamp Warranty 6 months or 1000 hours – whichever comes sooner Warranty Warranty will vary by country. Please see: www.optomaeurope.com or ask your local supplier for details Colour Guarantee³ 5 Years	Image Size	0.70 - 7.70m (27.49" - 303.12") Diagonal 4:3					
Power Supply 100 – 240V, 50 – 60Hz Power Consumption 233W BRIGHT mode < 1W Standby mode, 207W ECO mode < 1W Standby mode. Security Kensington Lock Port, Password Protection In the BOX Power Cord, VGA Cable, UM CD, Quick Start Guide, Remote, Batteries RoHS Compliant Lamp Warranty 6 months or 1000 hours — whichever comes sooner Warranty Warranty will vary by country. Please see: www.optomaeurope.com or ask your local supplier for details Colour Guarantee ³ 5 Years	Keystone	±40° Vertical					
Power Consumption 233W BRIGHT mode < 1W Standby mode, 207W ECO mode < 1W Standby mode. Security Kensington Lock Port, Password Protection In the BOX Power Cord, VGA Cable, UM CD, Quick Start Guide, Remote, Batteries Compliant Lamp Warranty Genoths or 1000 hours — whichever comes sooner Warranty Warranty will vary by country. Please see: www.optomaeurope.com or ask your local supplier for details Colour Guarantee ³ 5 Years	Operating Conditions Operating	5 - 35° C, 80% Humidity (Max), 3000m Altitude (Max)					
207W ECO mode < 1W Standby mode. Security Kensington Lock Port, Password Protection In the BOX Power Cord, VGA Cable, UM CD, Quick Start Guide, Remote, Batteries RoHS Compliant Lamp Warranty 6 months or 1000 hours — whichever comes sooner Warranty Warranty will vary by country. Please see: www.optomaeurope.com or ask your local supplier for details Colour Guarantee ³ 5 Years	Power Supply	100 – 240V, 50 – 60Hz					
Security Kensington Lock Port, Password Protection In the BOX Power Cord, VGA Cable, UM CD, Quick Start Guide, Remote, Batteries RoHS Compliant Lamp Warranty 6 months or 1000 hours — whichever comes sooner Warranty Warranty will vary by country. Please see: www.optomaeurope.com or ask your local supplier for details Colour Guarantee ³ 5 Years	Power Consumption	233W BRIGHT mode < 1W Standby mode,					
In the BOX Power Cord, VGA Cable, UM CD, Quick Start Guide, Remote, Batteries RoHS Compliant Lamp Warranty 6 months or 1000 hours — whichever comes sooner Warranty Warranty will vary by country. Please see: www.optomaeurope.com or ask your local supplier for details Colour Guarantee ³ 5 Years		207W ECO mode < 1W Standby mode.					
Remote, Batteries RoHS Compliant Lamp Warranty 6 months or 1000 hours – whichever comes sooner Warranty Warranty will vary by country. Please see: www.optomaeurope.com or ask your local supplier for details Colour Guarantee ³ 5 Years	Security	Kensington Lock Port, Password Protection					
RoHS Compliant Lamp Warranty 6 months or 1000 hours — whichever comes sooner Warranty Warranty will vary by country. Please see: www.optomaeurope.com or ask your local supplier for details Colour Guarantee ³ 5 Years	In the BOX	Power Cord, VGA Cable, UM CD, Quick Start Guide,					
Lamp Warranty 6 months or 1000 hours – whichever comes sooner Warranty Warranty will vary by country. Please see: www.optomaeurope.com or ask your local supplier for details Colour Guarantee ³ 5 Years		Remote, Batteries					
Warranty Warranty will vary by country. Please see: www.optomaeurope.com or ask your local supplier for details Colour Guarantee ³ 5 Years	RoHS	Compliant					
www.optomaeurope.com or ask your local supplier for details Colour Guarantee ³ 5 Years	Lamp Warranty	6 months or 1000 hours – whichever comes sooner					
for details Colour Guarantee ³ 5 Years	Warranty	Warranty will vary by country. Please see:					
Colour Guarantee ³ 5 Years		www.optomaeurope.com or ask your local supplier					
		for details					
Imager Guarantee ⁴ 5 Years	Colour Guarantee ³	5 Years					
	Imager Guarantee ⁴	5 Years					

EASY TO USE REMOTE CONTROL

DX211 Remote Control


- 1 Power
- 2 Vertical Keystone Correction
- 3 Volume Control
- 4 Brightness Adjustment
- 5 Digital Zoom
- 6 Contrast Adjustment
- 7 AV Mute
- 8 Freeze
- 9 Direct Input Source Selection

DX211 Connections

- 10 VGA SCART & Component
- 11 S-Video
- 12 Video
- 13 RS232 3 Pin
- 14 VGA Out
- **15** Kensington™ Lock



Exceptional Connectivity / Multiple Terminals



DX211 Distance Table Aspect Ratio 4:3									
Projection Distance (m)	Max. Horizontal Image Size (m)	Min. Horizontal Image Size (m)	Max. Vertical Image Size (m)	Min. Vertical Image Size (m)	Max Diagonal Image Size (m)	Max Diagonal Image Size (inch)	Max. Image Offset (m)		
1.20	0.62	0.56	0.46	0.42	0.77	30.31	0.07		
2.00	1.03	0.93	0.77	0.70	1.28	50.52	0.12		
2.50	1.28	1.16	0.96	0.87	1.60	63.15	0.14		
3.00	1.54	1.40	1.16	1.05	1.92	75.78	0.17		
4.00	2.05	1.86	1.54	1.40	2.57	101.04	0.23		
5.00	2.56	2.33	1.93	1.75	3.21	126.30	0.29		
6.00	3.08	2.79	2.31	2.10	3.85	151.56	0.35		
7.00	3.59	3.26	2.70	2.45	4.49	176.82	0.40		
8.00	4.10	3.72	3.08	2.80	5.13	202.08	0.46		
9.00	4.62	4.19	3.47	3.15	5.77	227.34	0.52		
10.00	5.13	4.65	3.86	3.50	6.42	252.60	0.58		
11.00	5.64	5.12	4.24	3.85	7.06	277.86	0.64		
12.00	6.15	5.58	4.63	4.20	7.70	303.12	0.69		

For guide purposes only

Optoma Europe Ltd.

42 Caxton Way, Watford Business Park, Watford, Hertfordshire, UK. WD18 8QZ

www.optoma.eu

