





From boardroom to classroom, the EX521 delivers bright, high contrast presentations and images with crystal clarity. Vibrant, life-like colours using BrilliantColor[™] technology will ensure your audience is left speechless every time the EX521 is turned on.

Whether travelling on business or having meetings away from the office, the convenient carry bag allows you to take the small and stylish EX521 from room to room or on the go with ease.

The environmentally friendly EX521 has energy saving features including <1W standby mode. Long lamp-life of 6000hrs combined with our unique Optoma Colour and Imager guarantees saves you both time and money while ensuring hassle-free, long lasting projection.

CLEAR, FOCUSED IMAGES

DarkChip3[™] technology from Texas Instruments produces a stunning 4500:1 contrast ratio for pin sharp, crystal clear images. Crisper whites and ultra rich blacks bring the image to life



1000:1 contrast ratio

4500:1 contrast ratio

[‡]Simulated Image

AMAZING COLOURS

The EX521 incorporates BrilliantColor™ technology to produce stunningly bright images with perfectly balanced life-like colours. Preset display modes allow you to achieve a perfect image every time.

COLOUR AND IMAGER GUARANTEE

Bright colours and fantastic image quality are guaranteed for an amazing 5 years after purchase - giving piece of mind that the technology inside the Optoma EX521 projector won't fade or degrade.



VIRTUALLY MAINTENANCE FREE

The EX521 provides lower cost of ownership, longer life and improved reliability. The filter-free projector design does not require regular filter cleaning or filter replacement, saving you time and money.





ENVIRONMENTALLY FRIENDLY

The EX521 incorporates energy saving features to conserve power and extend the lamp life:



To achieve the maximum 6000hrs² lamp life time the projector should be operating in ECO mode and the shut down timer should be enabled to automatically switch off the projector if it is accidentally left on when no longer required. Enabling the <1W Standby mode will ensure the minimum energy consumption when the projector is not being used.



It takes less than 10 seconds for the projector to power up and shutdown, saving both time and energy.

CONTROL

The extensive RS232 command set makes it simple and easy to control the EX521 with any control system.



AMX Compatibility – Dynamic Discovery Protocol is incorporated into the EX521. This feature allows for easy installation with AMX control systems.

SMOOTH, SEAMLESS PROJECTION

Even in the fastest moving scenes, the EX521 will project a smooth and seamless image. The rapid response of DLP[®] technology ensures that the projected movie or video game remains perfect and precise.





Without

FEATURES

- 6 preset display modes including Movie mode
- 4:3 and 16:9 widescreen
- Classroom mode 1500 ANSI Lumens
- Password protection for added security
- Ceiling mount the projector or project from a coffee table
- Easy to use remote with direct source control



Enjoy big bright pictures in the office, classroom day or night



We know that improving our products is the best way to reduce our impact on the environment. That's why at Optoma, we design our products to have a long usable life, use fewer materials, ship with the minimum packaging and be free of all possible toxic substances. Naturally, energy efficiency and being recyclable are built in at the design stage. With each new product, we strive towards minimising our environmental impact. For full details of Optoma Project Green please visit our website.

EX521 SPECIFICATIONS

| Native Resolution | XGA 1024 x 768 | | | | | |
|---------------------------------|--|--|--|--|--|--|
| Display Technology | 0.55" XGA DLP® chip, Technology by Texas Instruments | | | | | |
| Compatible Resolutions | UXGA, SXGA+, SXGA, WXGA, XGA, SVGA | | | | | |
| Brightness ¹ | 2600 ANSI Lumens | | | | | |
| Contrast Ratio | 4500:1 | | | | | |
| Lamp Life ² | 6000/5000 hours (ECO/BRIGHT mode) | | | | | |
| Noise Level | 28dB (ECO mode) | | | | | |
| Weight / Dimensions (W x D x H) | 2.3 kg / 286 x 192 x 84mm | | | | | |
| INPUTS | 15 Pin D-Sub VGA, SCART via adaptor, | | | | | |
| | Component via adaptor | | | | | |
| | S-Video 4 Pin Mini Din | | | | | |
| | Composite RCA Jack | | | | | |
| OUTPUT | 15 Pin D-Sub | | | | | |
| Control | RS232 3 Pin mini-DIN | | | | | |
| Aspect Ratio | 4:3 Native, 16:9 compatible | | | | | |
| On Screen Display | 17 Languages: English, German, French, Italian, Spanish, | | | | | |
| | Portuguese, Polish, Dutch, Russian, Finnish, Swedish, | | | | | |
| | Greek, Norwegian/Danish, Hungarian, Czech, | | | | | |
| | Turkish and Arabic | | | | | |
| Video Compatibility | PAL SECAM 625/576i\p, NTSC 525/480i\p | | | | | |
| nace company | HD 720p/1080i/p | | | | | |
| Uniformity | 85% | | | | | |
| Zoom | 1.1x Manual Zoom | | | | | |
| Projection Distance | 1.2 – 12m | | | | | |
| Image Size | 0.70 – 7.70m (27.49" – 303.12") Diagonal 4:3 | | | | | |
| Keystone | ±40° Vertical | | | | | |
| Operating Conditions Operating | 5 - 35° C, 80% Humidity (Max), 3000m Altitude (Max) | | | | | |
| Power Supply | 100 – 240V, 50 – 60Hz | | | | | |
| Power Consumption | 233W BRIGHT mode < 1W Standby mode, | | | | | |
| | 207W ECO mode < 1W Standby mode. | | | | | |
| Security | Kensington Lock Port, Password Protection | | | | | |
| In the BOX | Carry Bag, Power Cord, VGA Cable, UM CD, Quick Start | | | | | |
| - | Guide, Remote, Batteries | | | | | |
| RoHS | Compliant | | | | | |
| Lamp Warranty | 6 months or 1000 hours – whichever comes sooner | | | | | |
| Warranty | Warranty will vary by country. Please see: | | | | | |
| , | www.optomaeurope.com or ask your local supplier | | | | | |
| | for details | | | | | |
| Colour Guarantee ³ | 5 Years | | | | | |
| Imager Guarantee ⁴ | 5 Years | | | | | |
| | | | | | | |

EASY TO USE REMOTE CONTROL

EX521 Remote Control

- 1 Power
- 2 Vertical Keystone Correction3 Volume Control
- 3 Volume Control4 Brightness Adjustment
- 5 Digital Zoom
- 6 Contrast Adjustment
- 7 AV Mute
- 8 Freeze
- 9 Direct Input Source Selection

EX521 Connections

- 10 VGA SCART & Component
- 11 S-Video
- 12 Video
- 13 RS232 3 Pin
- 14 VGA Out
- **15** Kensington[™] Lock



Exceptional Connectivity / Multiple Terminals



| Projection Distance (m) | Max. Horizontal Image Size (m) | Min. Horizontal Image Size (m) | Max. Vertical Image Size (m) | Min. Vertical Image Size (m) | Max Diagonal Image Size (m) | Max Diagonal Image Size (inch) | Max. Image Offset (m) |
|-------------------------|-----------------------------------|-----------------------------------|------------------------------|------------------------------|--------------------------------|-----------------------------------|-----------------------|
| 1.20 | 0.62 | 0.56 | 0.46 | 0.42 | 0.77 | 30.31 | 0.07 |
| 2.00 | 1.03 | 0.93 | 0.77 | 0.70 | 1.28 | 50.52 | 0.12 |
| 2.50 | 1.28 | 1.16 | 0.96 | 0.87 | 1.60 | 63.15 | 0.14 |
| 3.00 | 1.54 | 1.40 | 1.16 | 1.05 | 1.92 | 75.78 | 0.17 |
| 4.00 | 2.05 | 1.86 | 1.54 | 1.40 | 2.57 | 101.04 | 0.23 |
| 5.00 | 2.56 | 2.33 | 1.93 | 1.75 | 3.21 | 126.30 | 0.29 |
| 6.00 | 3.08 | 2.79 | 2.31 | 2.10 | 3.85 | 151.56 | 0.35 |
| 7.00 | 3.59 | 3.26 | 2.70 | 2.45 | 4.49 | 176.82 | 0.40 |
| 8.00 | 4.10 | 3.72 | 3.08 | 2.80 | 5.13 | 202.08 | 0.46 |
| 9.00 | 4.62 | 4.19 | 3.47 | 3.15 | 5.77 | 227.34 | 0.52 |
| 10.00 | 5.13 | 4.65 | 3.86 | 3.50 | 6.42 | 252.60 | 0.58 |
| 11.00 | 5.64 | 5.12 | 4.24 | 3.85 | 7.06 | 277.86 | 0.64 |
| 12.00 | 6.15 | 5.58 | 4.63 | 4.20 | 7.70 | 303.12 | 0.69 |

For guide purposes only

Optoma Europe Ltd.

www.optoma.co.uk

42 Caxton Way, Watford Business Park, Watford, Hertfordshire, UK. WD18 8QZ





¹Brightness and lamp lifetime will vary depending on selected projector mode, environmental conditions and usage. As is common with all lamp based projectors, brightness will decrease over the lamp lifetime. ²Typical lamp life achieved through testing, Will vary according to operational use and environmental conditions. ²Optoma guarantees that in normal use, Optoma DLP® colour quality will be indistinguishable from when new. Exclusions: (a) Guarantee is voided if the projector is subject to damage through misuse. (b) Guarantee may be void in industrial or commercial entertainment environments where dust or smoke is excessive (c) Guarantee will not apply if lamp brightness is below 50% due to wear or if the projector is out orking due to other faults. (d) Over time worn lamps within all projector types will show a slight colour variance. ⁴Optoma guarantees that in normal use, the DLP[®] imager will retain image quality for at least 5 years and provide consistent pixel performance. Exclusions: (a) Guarantee is worded if the projector is subject to damage through misuse. (b) Guarantee may be void in industrial or commercial entertainment, where dust or smoke is excessive. Copyright © 2011, Optoma Europe Ltd. All other product names and company names used herein are for identification purposes only and may be trademarks or the irrespective owners. Errors and omissions excepted, all specifications are subject to change without notice. DLP[®], BrillianColor[™] and the DLP log or are engistered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. DLP[®], Brillian Color[™] and the DLP log or are engistered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. DLP[®], Brillian Color[™] and the DLP log or are engistered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. DLP[®], Brillian Color[™]