



M1Active MK2 Product Overview



Product Description

By combining our expertise in reference monitor design with our proven track record in studio amplification, Alesis' new M1 Active™ Bi-amplified Reference Monitor offers the incredibly accurate response that perfectly translates to every playback system. Its internal active crossover and custom-designed dual amplifiers ensure an extremely consistent performance under a variety of different studio conditions and program material. The result is a broad, extremely flat frequency response, clear imaging with a wide sweet spot, high power handling and detailed high- and mid-frequency response that only a professional powered monitor can deliver.

With the lineage of our TEC Award-winning Monitor One Studio Reference Monitor, Alesis speakers have already become a standard in project and professional studios around the world. If you're looking for the same great accuracy and detailed response in a powered system that's truly affordable, the answer is clear: the new M1 Active from Alesis.

Key Features and Benefits

Low Frequency Driver:

6.5" non-woven carbon fiber with Santoprene surround and dual magnet shielded configuration

High Frequency Driver:

1" silk dome with medium viscosity ferrofluid coolant and dual magnet shielded configuration

Crossover:

1500Hz, 8th-order, 48dB/octave filters

Input Impedance:

20k_ balanced,
10k_ unbalanced

Frequency Range:

38 Hz - 23.5 kHz (-10dB point)

Connectors:

Combination XLR-1/4" jack with input level control

Dimensions:

(WxHxD) 8.5"x15"x9.75"
(381mm x 216mm x 248mm)

Weight:

19.5 lbs. (8.9kg) each