

SPECIFICATIONS

Operating levels

Main outputs	+4dBu XLR
Monitor	0dBu RCA
FX sends	-2dBu RCA
Maximum output level	+26dBu
Mic Sensitivity	-45 to -15dBu
RIAA input sensitivity	7-100mV 47K/330pF
Frequency response Line in to Mix out	20 Hz to 30KHz +0/-2dB
Distortion at 1kHz Line in at +0Vu out	<0.02%
Main Mix noise 22Hz— 22KHz unweighted	<-80dBu (84dB S/N)
Residual Mix noise 22Hz— 22KHz unweighted	<-97dBu
Equalization	3-band +6dB/off (kill), 120Hz, 1.2kHz, 10kHz
Fader Shutoff	<-90dB

Dimensions and Weights

The console is fitted with rubber feet for desktop operation. A screw on rack ear kit is included for 19" rack or plinth mounting.

	Width	Height	Depth	Weight
Desktop	432 mm (17")	88 mm (3.5")	358 mm (14")	5kg (11 lbs)
Rack ears fitted	483 mm (19")	88 mm (3.5")	358 mm (14")	
Packed	575 mm (22.6")	195 mm (7.7")	490 mm (15.7")	6 kg (13.2 lbs)

Rack ears allow permanent fixing in a plinth or rack system. They can be fitted two ways; either with the flange flush with the top panel or flush with the underside of the chassis. The rack ears are fixed in place using the 6x M4 screws provided. Ensure that air vents are not obstructed.

