



The SDQ5 loudspeaker design will definitely become an established value in the contactor market!

Its discrete design is in perfect harmony with the transparent sound exhibited.

The loudspeaker is equipped with a U-bracket. As the SDQ5 has the 1 step protection guard build-in, the loudspeaker is protected from overloads. This all makes the SDQ5 loudspeaker suited for dispersion of backgroundmusic and microphone calls.

The SDQ5 loudspeakers are available in 3 different colours: black (Ref; SDQ5-BL), white (Ref; SDQ5-W) and silver (SDQ5-SLV). As an option, the SDQ5 loudspeakers can be painted in any RAL colour (Ref; PAINT-CAB6). Please note that the minimum order quantity for PAINT-CAB6 is 12 pieces.

## TECHNICAL SPECIFICATIONS

|                        |                            |
|------------------------|----------------------------|
| Type                   | 2-way HiFi Pro, sealed box |
| Cabinet                | Enforced poly plastic      |
| Woofer                 | 5.25" CP type              |
| Tweeter                | 1" mylar ferro cooled      |
| Impedance              | 8 Ohm                      |
| RMS Power 8 Ohm        |                            |
| AES Rated              | 70 watt                    |
| Music - Program        | 100 watt                   |
| Dynamic Peak (lo-cut)  | 250 watt                   |
| Protection system      | Auto-Reset 1 Guard         |
| SPL 1 watt/1 m         | 91 dB                      |
| SPL Max peak           | 115 dB                     |
| Frequency Range        | 70 Hz - 20 kHz             |
| Speaker connectors     | Push terminals             |
| Dispersion             | 120° H x 100° V            |
| IP rating              | 50                         |
| Dimensions (H x W x D) | 244 x 179 x 154 mm         |
| Weight                 | 2.07 Kg                    |