Recording Products



TRUTH B3030A Active Ribbon Studio Monitors



0	I I			•			•	
			INTER BI-AMPLI 75 W 35 W	WARP TO REDUCE OF FILE ON SHOCK OD I EQUIDATION OF MOSTUL REFERSION QUILLED P	WARM THE COUPE IS CANUEL DELMERING PRESENT DOCESS OF WHICH MIL PREMIMEN HEARING D		2-WAY	
	BEI M		97 H	THE REX ELECTRIC NOT 5 TO RAIN RE ADDING TO EFEOTNEL	MENT 10F 12DUND 12MLE N 80 88 7 CAUSE 17 AMWCZ	DED-FFINGE a.behringer	RL ACTIVE RI	ĮЩ
AMERI.	A TYPICAL ARINGER TRI IODEL B3030	5335	LOW FREQUING ADAPT MONITO TRADAPT MONITO TO AN ADOTTONAL SUBMODIFIC ON TO SUBMODIFIC ON TO SUBMODIFIC DIALS	-3.0 -3.0		.com	BBON STUDI	ųų.
			11 4	7 :		ر ۱۹۹		ųa,
CAUTION			ROON COMPENSION MONTON PLO			(NAM
. E 1	A _				NURROW 468		-	
ER SOUR	CAUTION		HIGH FRE	200 200 200 400		I. NUMBER	_	
3	~ A		MITTER					<u>III</u>
	Ĭ	ļ					R	
				0				

Sold as Matched Pair

2-Way Active Ribbon Studio Reference Monitor with Kevlar Woofer

- Ultra-linear frequency response with individual frequency diagrams
- Built-in 75 and 35-Watt power amplifiers with enormous power reserve
- Ultra-high resolution, 2" velocity ribbon transducer for ultimate sound reproduction
- Long-throw 6 ³/₄" woofer with deformation-resistant Kevlar cone and aluminum die-cast chassis for ultimate bass response
- Controlled dispersion characteristics and extremely large "sweet spot" owing to the unique BEHRINGER wave guide technology
- Active crossover network with 4th order Linkwitz-Riley filters
- Adjustable to a wide range of acoustic conditions and subwoofer operation
- Separately controlled limiter for low and high-frequency overload protection
- Magnetic shielding allows placement near computer monitors
- Delivered as "matched pairs" with individual frequency diagrams
- Servo-balanced inputs with XLR and 1/4" TRS connectors
- High-quality components and exceptionally rugged construction ensure long life
- Conceived and designed by BEHRINGER Germany