

EUROLIVE E1520A

Specifications

71633-00001

en



www.behringer.com



EUROLIVE

Processor-Controlled 400-Watt 2-Way PA Loudspeaker/Floor Monitor

- ▲ High-power 400-Watt 2-way PA sound reinforcement speaker/floor monitor for live and playback applications
- ▲ Exceptional sound quality, wide frequency bandwidth and extensive dynamic range
- ▲ Integrated sound processor for ultimate system control and speaker protection
- ▲ Extremely powerful 12"/15" long-excursion driver provides incredibly deep bass and acoustic power
- ▲ Proprietary 1" HF driver for exceptional high-frequency reproduction
- ▲ Ultra-low noise Mic/Line input with Volume control and Clip LED
- ▲ Additional Line output allows linking of additional speaker systems
- ▲ Versatile enclosure profile allows different positioning:
 - 10 & 35 degree cluster and stacking mode
 - Stand mounting with 35-mm pole socket
 - Floor monitor wedge
- ▲ Ergonomically shaped handles for easy carrying and setup
- ▲ Rugged steel grill for optimal speaker protection
- ▲ High-quality components and exceptionally rugged construction ensure long life
- ▲ Conceived and designed by BEHRINGER Germany

E1520A

Specifications**Output power****Low-frequency range**

RMS @ 1% THD	200 W @ 8 Ω
Peak power	320 W @ 8 Ω

High-frequency range

RMS @ 1% THD	50 W @ 8 Ω
Peak power	80 W @ 8 Ω

Input**XLR connector (servo-balanced)**

Sensitivity	-40 to +4 dBu
Input impedance	24 kΩ

1/4" jack (servo-balanced)

Sensitivity	-40 to +4 dBu
Input impedance	24 kΩ

Link output**XLR connector****System data**

Frequency range	50 Hz to 20 kHz
Crossover frequency	2 kHz (12 dB)
Maximum sound pressure level	125 dB @ 1 m
Limiter	optical
Dynamic Equalizer	Processor-controlled

Equalizer

HIGH	12 kHz / ± 15 dB
LOW	80 Hz / ± 15 dB

Power supply**Mains voltage/fuses**

100 -120 V~, 50/60 Hz	T 5,0 A H 250 V
220 -230 V~, 50/60 Hz	T 2,5 A H 250 V

Power consumption	max. 400 W
Mains connector	Standard IEC receptacle

Dimensions/Weight

Dimensions (H x W x D)	approx. 465 x 485 x 640 mm approx. 18.3" x 19" x 25.2"
Weight	approx. 26.3 kg approx. 58 lbs.

BEHRINGER is constantly striving to maintain the highest professional standards. As a result of these efforts, modifications may be made from time to time to existing products without prior notice. Specifications and appearance may differ from those listed or illustrated.

Technical specifications and appearance are subject to change without notice. The information contained herein is correct at the time of printing. BEHRINGER accepts no liability for any loss which may be suffered by any person who relies either wholly or in part upon any description, photograph or statement contained herein. Colors and specifications may vary slightly from product. Our Products are sold through authorized dealers only. Distributors and dealers are not agents of BEHRINGER and have absolutely no authority to bind BEHRINGER by any express or implied undertaking or representation. This manual is copyrighted. No part of this manual may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording of any kind, for any purpose, without the express written permission of BEHRINGER International GmbH.

ALL RIGHTS RESERVED.

© 2008 BEHRINGER International GmbH, Hanns-Martin-Schleyer-Str. 36-38, 47877 Willich-Muencheide II, Germany,
Tel. +49 2154 9206 0, Fax +49 2154 9206 4903
