

# PMP518M

# EUROPOWER

## Technical Specifications

en

Version 1.0 February 2007



[www.behringer.com](http://www.behringer.com)



# EUROPOWER

Ultra-Compact 180-Watt 5-Channel Powered Mixer with Multi-FX Processor and FBQ Feedback Detection System



- ▲ Super-compact rackmountable 180-Watt powered mixer with 24-bit FX processor
- ▲ Revolutionary amplifier technology: enormous power, incredible sonic performance and super-light weight
- ▲ Ultra-compact design at nearly half the depth and weight of conventional powered mixers means no more lugging around dead weight
- ▲ Ultra-low noise ULN design for highest possible headroom and ultra-transparent audio
- ▲ 5-channel mixer section features 5 mic/line channels plus separate 2-track in/output
- ▲ Integrated 24-bit digital FX processor with 100 awesome presets including reverb, chorus, flanger, delay, pitch shifter and various multi-effects
- ▲ Revolutionary FBQ Feedback Detection system instantly reveals critical frequencies for easy feedback removal
- ▲ 5 high-quality mic preamps with switchable Pad and Clip LEDs
- ▲ Effective, extremely musical 2-band EQ on all channels
- ▲ 7-band graphic EQ allows precise frequency correction
- ▲ 3 speaker outputs on 1/4" jack and professional speaker connectors (compatible with Neutrik Speakon connectors)
- ▲ Rack mount brackets included
- ▲ High-quality components and exceptionally rugged construction ensure long life
- ▲ Conceived and designed by BEHRINGER Germany

\* All trademarks (except BEHRINGER, the BEHRINGER logo, JUST LISTEN, EUROPOWER and FBQ) mentioned belong to their respective owners and are not affiliated with BEHRINGER

## SPECIFICATIONS

### MICROPHONE INPUTS

Type	XLR, electronically balanced
Mic E.I.N. (20 Hz - 20 kHz)	
@ 0 $\Omega$ source resistance	-122 dB / -125 dB A-weighted
@ 50 $\Omega$ source resistance	-122 dB / -125 dB A-weighted
@ 150 $\Omega$ source resistance	-121 dB / -124 dB A-weighted
Frequency response	< 10 Hz - 100 kHz (-1 dB), < 10 Hz - 200 kHz (-3 dB)
Gain	+33 dB, +8 dB with pad
Max. input level	+12 dBu @ 10 dB gain
Impedance	approx. 2.2 k $\Omega$ balanced, 1.1 k $\Omega$ unbalanced
Signal-to-noise ratio	110 dB / 114 dB A-weighted (-11 dBu in @ +33 dB gain)
Distortion (THD+N)	0.001% / 0.0008% A-weighted

### MONO LINE INPUTS

Type	¼" TRS connector, balanced
Impedance	approx. 80 k $\Omega$ balanced, 40 k $\Omega$ unbalanced
Max. input level	+30 dBu

### EQ

Low	80 Hz / $\pm 15$ dB
High	12 kHz / $\pm 15$ dB

### MAIN MIX SYSTEM DATA

Noise	
Main mix @ - $\infty$ , Channel fader - $\infty$	-106 dB / -110 dB A-weighted
Main mix @ 0 dB, Channel fader - $\infty$	-87 dB / -90 dB A-weighted
Main Mix @ 0 dB, Channel fader @ 0 dB	-80 dB / -82 dB A-weighted

### LOUDSPEAKER OUTPUTS

Type	Neutrik Speakon-compatible, ¼" TS connectors
Load impedance	4 - 16 $\Omega$

### DSP

Converter	24-bit Sigma-Delta,
Sampling rate	40 kHz

### DISPLAY

Type	2-digit, 7-segment LED
------	------------------------

### AMPLIFIER

Output power (RMS @ 1 % THD (sine wave))	62 W (8 $\Omega$ ), 105 W (4 $\Omega$ )
Output power (Peak Power)	100 W (8 $\Omega$ ), 180 W (4 $\Omega$ )

### POWER SUPPLY

Mains voltages	U.S./Canada 120 V~, 60 Hz China/Korea 220 V~, 50/60 Hz Europe/U.K./Australia 230 V~, 50 Hz Japan 100 V~, 50 - 60 Hz General export model 120/230 V~, 50 - 60 Hz
Power consumption	max. 290 W
Fuse	100 - 120 V~: T 6.3 A H 250 V 220 - 240 V~: T 3.15 A H 250 V
Mains connection	Standard IEC receptacle

### PHYSICAL/WEIGHT

Dimensions (H x W x D)	approx. 4 3/5" x 18 1/2" x 8 7/8" (117 mm x 470 mm x 225 mm)
Weight (net)	approx. 15.88 lbs (7.2 kg)

en

BEHRINGER is constantly striving to maintain the highest professional standards. As a result of these efforts, modifications may be made from time to time to existing products without prior notice. Specifications and appearance may differ from those listed or illustrated.

Technical specifications and appearance are subject to change without notice. The information contained herein is correct at the time of printing. All trademarks (except BEHRINGER, the BEHRINGER logo, JUST LISTEN and EUROPOWER) mentioned belong to their respective owners and are not affiliated with BEHRINGER. BEHRINGER accepts no liability for any loss which may be suffered by any person who relies either wholly or in part upon any description, photograph or statement contained herein. Colors and specifications may vary slightly from product. Products are sold through our authorized dealers only. Distributors and dealers are not agents of BEHRINGER and have absolutely no authority to bind BEHRINGER by any express or implied undertaking or representation. No part of this manual may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording of any kind, for any purpose, without the express written permission of BEHRINGER International GmbH.

ALL RIGHTS RESERVED. © 2007 BEHRINGER International GmbH.  
BEHRINGER International GmbH,  
Hanns-Martin-Schleyer-Str. 36-38, 47877 Willich-Muenchheide II, Germany.  
Tel. +49 2154 9206 0, Fax +49 2154 9206 4903