

EUROLIVE S1020/S1220/S1220F/S1520/S1530/S1800S

Technical Specifications

en

Version 1.0 December 2006



www.behringer.com



EUROLIVE

High-Performance PA Speaker System

- ▲ Exceptional sound quality, wide frequency bandwidth and dynamic range
- ▲ Extremely powerful long-excursion drivers provide incredibly deep bass and acoustic power
- ▲ State-of-the-art dual electro-dynamic drivers for exceptional high-frequency reproduction (except S1800S)
- ▲ Overload-protection circuitry ensures optimal HF driver protection
- ▲ Elliptical wave guide design for ultra-wide sound dispersion (except S1800S)
- ▲ Ergonomically shaped handles for easy transport
- ▲ Rugged steel grill for optimal speaker protection
- ▲ 2 professional ¼" jack connectors
- ▲ High-quality components and exceptionally rugged construction ensure long life
- ▲ Conceived and designed by BEHRINGER Germany

SERIES

SPECIFICATIONS

	S1020	S1220	S1220F	S1520	S1530	S1800S
SYSTEM DATA						
Continuous Power (IEC268-5)	60 W	70 W	70 W	90 W	100 W	175 W
Peak Power	240 W	280 W		360 W	400 W	700 W
Type	2-way full-range speaker				3-way full-range speaker	subwoofer
Frequency response	60 Hz – 20 kHz	50 Hz – 20 kHz				45 Hz – 400 Hz
Impedance	8 Ohm					4 Ohm
Sound pressure level	98 dB (Full Space, 1 W @ 1 m)					98 dB (1 W @ 1 m)
Dispersion	90° x 40°					-
Crossover frequency	3.5 kHz				1.5 kHz 3.5 kHz	- (350 Hz recommended)
Rigging/fittings	- ergonomically shaped handles - integral tripod and stand adapter		- ergonomically shaped handle	- ergonomically shaped handles - integral tripod and stand adapter		- ergonomically shaped handles - pole socket
COMPONENTS						
HF driver	Dual electro-dynamic drivers					-
Mid driver	-	-	-	-	6.5" (167 mm)	-
Woofers	10" (259 mm)	12" (307 mm)		15" (385 mm)	15" (385 mm)	18" (460 mm)
DIMENSIONS/WEIGHT						
Width	12.2 / 6.7" (311 / 170 mm)	16.9" / 10.4" (428 / 264 mm)	16.9" (428 mm)	18.2" / 11.4" (463 / 289 mm)	20.6 / 12.9" (523 / 327 mm)	21.3" (541 mm)
Height	19.3" (490 mm)	21.8" (554 mm)	21.7" (550 mm)	24.6" (624 mm)	28.7" (729 mm)	28.9" (735 mm)
Depth	11.1" (282 mm)	13.2" (335 mm)	14.6" / 4.5" (371 / 115 mm)	13.7" (347 mm)	15.5" (393 mm)	15.8" (400 mm)
Weight	19.8 lbs (9 kg)	29.3 lbs (13.3 kg)	28.7 lbs (13 kg)	38.8 lbs (17.6 kg)	52.9 lbs (24 kg)	68.3 lbs (31 kg)
Shipping weight	22.5 lbs (10.2 kg)	33.1 lbs (15 kg)	33.1 lbs (15 kg)	41.9 lbs (19 kg)	56.2 lbs (25.5 kg)	72.8 lbs (33 kg)

en

BEHRINGER is constantly striving to maintain the highest professional standards. As a result of these efforts, modifications may be made from time to time to existing products without prior notice. Specifications and appearance may differ from those listed or illustrated.

Technical specifications and appearance subject to change without notice. The information contained herein is correct at the time of printing. All trademarks (except BEHRINGER, the BEHRINGER logo, JUST LISTEN, EUROLIVE and EUROPOWER) mentioned belong to their respective owners, and such use neither constitutes a claim of the trademarks by BEHRINGER nor affiliation of the trademark owners with BEHRINGER. BEHRINGER accepts no liability for any loss which may be suffered by any person who relies either wholly or in part upon any description, photograph or statement contained herein. Colors and specifications may vary slightly from product. Products are sold through our authorized dealers only. Distributors and dealers are not agents of BEHRINGER and have absolutely no authority to bind BEHRINGER by any express or implied undertaking or representation. No part of this manual may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording of any kind, for any purpose, without the express written permission of BEHRINGER International GmbH.

ALL RIGHTS RESERVED. © 2006 BEHRINGER International GmbH,
Hanns-Martin-Schleyer-Str. 36-38, 47877 Willich-Münchheide II, Germany.
Tel. +49 2154 9206 0, Fax +49 2154 9206 4903