AVD 08 Relay Unit



FEATURES:

Added value ARU Units

8 switching relays for any switching application

Mounted on DIN-rail

APPLICATIONS:

Activation emergency call, switching of 24 V DC Control of relays (door contacts...), power on delay for heavy sound systems...

Must be combined with AUDAC APM Paging consoles, can be combined with other units or AVD-versions

AVD 08

The AVD switching units are an added value to the ARU units of AUDAC.

They are designed to switch a common input signal to a certain output.

This relay unit is fitted with 8 switching relays which can be configured for any switching application by means of the built-in micro controller.

This unit must be combined with the AUDAC APM paging consoles, giving a simple and fast set-up. The unit is standard mounted on DIN-rail with simple connectors for the common input signal and the "zone output connectors".

Due to this mounting, a cable connector board is immediately created when building 19 " racks. Through addressing, it is possible to connect multiple units in series or parallel or to combine the unit with other AVD-versions.

All the relays are fitted standard with "status leds" enabling operation conditions to be easily controlled.

The AVD-08 works on a 24 V DC power supply and the relays are activated according to the principle of grounding (common line).

grounding (common line).
Through the RS485 data bus, communication with the APM paging tables or other control equipment is established (e.g. Crestron, AMX,...).
Most known applications for the AVD units are:

Most known applications for the AVD units are : Activation of the "Emergency call" relay on volume controls.

Switching of 24 V DC Control of (power)relays for

doorcontacts, ...

Power on delay for heavy sound systems with many high power amplifiers (i.e. 8 amps of 4800 W). A delayed power control can be set up with the AVD units. The time delay is adjustable.

| PRODUCT FEATURES: | |
|------------------------|-------------------|
| Number of relays | 8 |
| Dimensions (BxHxD) | 205 x 98 x 125 mm |
| Weight | 0.500 kg |
| Height | 100 mm |
| Standard data bus | RS485 |
| Fire hazard class | VO (UL94) |
| Unbreakable housing | |
| SYSTEM SPECIFICATIONS: | |
| Power supply | 24V DC |
| Input mains power | 6W |
| VERSIONS: | |
| AVD 04 | 4 relays |
| AVD 08 | 8 relays |
| AVD 16 | 16 relays |

AUDAC provides a complete range of audio equipment such as amplifiers, loudspeakers, microphones, conference microphones and much more.

