

CS 55

Ceiling Speaker



CS 55

CS 55

Installation ceiling loudspeaker that is generally used for large projects. The double cone loudspeaker with a diameter of 125 mm ensures a good speech reproduction.

Below the detachable steel grid, there are four screws for a quick and simple attachment of the unit.

The aluminium grid, when replaced, effectively covers the fixing screws.

The loudspeaker is standard fitted with a 100 Volt line transformer and with connections for different powers.

FEATURES :

Installation ceiling loudspeaker

Double cone loudspeaker

Detachable steel grid

Fitted with aluminium grid

Suitable for various powers

APPLICATIONS :

These loudspeakers are generally used for large projects

Very good speech reproduction

PRODUCT FEATURES :

Outside diameter	200 mm
Installation depth	70 mm
Cut-out measurement	165 mm
Colour	White RAL 9010
Weight	1 kg
Option	Available in other RAL colours

SYSTEM SPECIFICATIONS :

Nominal Speaker Power:	15 W
Sound pressure 1W / 1m	90 dB
Maximum SPL	100.8 dB
Impedance Loudspeaker	8 Ohm
Impedance line transformer	1.600 Ohm/ 6 W 3.300 Ohm/ 3 W 6.600 Ohm/1.5 W
Frequency range	70 - 14.000 Hz

About Audac :

AUDAC provides a complete range of audio equipment such as amplifiers, loudspeakers, microphones, conference microphones and much more.