

CS 75

Ceiling Speaker



CS 75

CS 75

Extremely high-quality ceiling loudspeaker for installation. The 2-way loudspeaker with a diameter of 125 mm for low frequencies and a tweeter, mounted in the middle, for high frequencies ensures a brilliant reproduction of all kinds of music. The loudspeaker has had a moisture-proof treatment. Because the grid is made of aluminium, the loudspeaker can be placed in damp rooms or outside. Below the detachable grid, there are 4 screws for a quick and simple mounting. The grid, when replaced, effectively covers the fixing screws. The loudspeaker is standard fitted with a 100 Volt line transformer with different power connections.

FEATURES :

High-quality 2-way ceiling loudspeaker + tweeter

Quick and simple mounting

Detachable, aluminium grid

APPLICATIONS :

Can be used inside as well as in damp rooms or outside

Brilliant reproduction of all kinds of music

PRODUCT FEATURES :

Outside diameter	200 mm
Installation depth	85 mm
Cut-out diameter	165 mm
Colour	White RAL 9010
Weight	1.1 kg
Options	Available in other RAL colours

SYSTEM SPECIFICATIONS :

Nominal Speaker Power	40 W
Sound pressure 1W / 1m	97 dB
Maximum SPL	105 dB
Impedance Loudspeaker	8 Ohm
Impedance line transformer	8 Ohm 400 Ohm / 24 W 800 Ohm / 12 W 1,6 KOhm / 6 W
Frequency range	60 - 21 kHz

About Audac :

AUDAC provides a complete range of audio equipment such as amplifiers, loudspeakers, microphones, conference microphones and much more.