

GIAX

Column Speaker

AUDAC

► Features

- Slim line ALU design
- Clear and crisp sound reproduction.
- Mounting bracket included
- Light weight
- Timeless design
- Wide distribution field (170°)
- 24 High Quality 2" drivers
- Aluminium front finish

► Applications

- Indoor applications
- Auditoria
- Churches
- Meeting and board rooms
- Wide frequency range applications

The AUDAC column speaker "GIAX" is designed to meet the requirements of professional installers for auditoria, airport lounges, conference rooms, places of worship, etc...

Anywhere where a great flexibility in positioning (almost 180°) and long distance sound projection is necessary.

The GIAX column speaker is a line array of 24 special designed 2 inch drivers, which are located on precisely calculated locations in the speaker column.

The line array method gives the listener the impression he's listening to just a single sound source but with a more distributed sound coverage throughout the room.

Inside this column speaker, four groups of drivers will accomplish a wide dispersion horizontally. These drivers will also achieve the desired directivity and very directional vertical coverage.

The GIAX has a surprisingly powerful output but with a state-of-the-art audio quality.

Its design features an aluminum housing, what results in a light weight column speaker of approximately 6,5 Kg

For mounting the AUDAC GIAX speaker, a specially designed wall bracket is included, which makes it possible to focus the speaker in any direction, to obtain the best possible audibility.

The GIAX will be available in white and black colour:

- Black: GIAX/B
- White: GIAX/W

► Specifications

PRODUCT FEATURES	
Dimensions (WidthxHeightxDensity)	70 x 2005 x 105 mm
Weight net	6,5 Kg
Drivers	24 x 2"
Construction	Aluminium
Front finish	Aluminium grill
Colour	Black (RAL9005) / GIAX/B White (RAL9010) / GIAX/W
SYSTEM SPECIFICATIONS	
Max. power	480 W
RMS power	240 W
Impedance	4 Ohm
Sound pressure 1W / 1m	90 dB
Sound pressure Max. W / 1m	106 dB
Frequency response -3dB	100 Hz - 17 kHz
Frequency response -10 dB	80 Hz - 19 kHz
Horizontal coverage	170°
SHIPPING & ORDERING	
Packaging	Carton box
Shipping weight & volume	7,8 Kg - 0.007 Cbm
Accessories included	Wall bracket
*AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our products	