

LX503

Wall Speaker

AUDAC

► Features

- 3-Way active + passive speaker
- Bass and Treble equalization
- Adjustable brackets
- Good quality speaker
- Easy to mount on walls/ceilings
- Wide frequency range
- Heat sink for cooling
- Line level amplification

► Applications

- Shops
- Warehouses
- Bars
- Restaurants
- Offices



The LX503 is AUDAC's first active, 3-way wall speaker. This speaker is available in white and black colour.

Due to its power handling of 75W, the LX503 will be powerful and very flexible for many indoor applications. The main speaker will need 230V AC supply voltage via an Euronet cable.

At the back of this speaker, you will find all the control functions:

A Volume potmeter for adjusting the level of loudness, Bass and/or Treble regulation for basic equalization and an On/Off power switch.

A stereo line level signal can be fed into two Cinch unbalanced connectors or one stereo mini jack connector.

A line level signal coming from a CD, DVD, VHS, Tuner or Mixing desk is applied into two RCA connectors. The stereo mini jack input works great for use with iPod, MD, MP3 players, etc...

With the powered LX503 speaker comes a second passive 8 Oms speaker which can be connected via the Euro Terminal block from the active LX503 speaker and the two speaker taps from the passive LX503 speaker.

Both speakers have a bracket made from sturdy steel, finished with powder coating.

► Specifications

PRODUCT FEATURES		
Dimensions (WidthxHeightxDensity)	178 x 240 x 193 mm	
Weight net (both speakers)	5.4 Kg	
Drivers	HF	3/4"
	MF	1"
	LF	5 1/4"
Construction	ABS	
Bracket	Coated steel	
Colours	Black	LX503/B
	White	LX503/W
SYSTEM SPECIFICATIONS		
RMS power	2 X 35 W	
Power handling	75 W	
Sensitivity	88 dB	
Frequency response	80 Hz - 20 kHz	
SHIPPING & ORDERING		
Packaging	Carton box	
Shipping weight & volume (2pcs)	6.5 Kg - 0.0082 Cbm	
*AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our products		