

# RX 115

## Speaker Cabinet



RX115

### FEATURES :

High-fidelity, full range reproduction of music and speech

Application-specific coverage pattern

### APPLICATIONS :

Full range speaker cabinet for in-and outdoor road touring applications

## RX115

The AUDAC ® RX115 cabinets are a new generation of compact, full range loudspeakers especially designed for live in- and outdoor applications.

The advantage of this system, combining state-of-the-art technology with revolutionary engineering design, is that it includes loudspeakers with high sensitivity and low distortions, which results in high fidelity sound.

The RX115 contains a special modified constant directivity horn with a 1.3 " HF compression driver and a 15 " high power low frequency loudspeaker and is designed to work in a vertical as well as a horizontal plan, with a coverage pattern of 90 x 75.

Average power handling shall be 600W peak.  
On-axis frequency range shall be of 75 Hz to 18 kHz.  
On-axis sensitivity (1W / 1m) shall be 99 dB SPL and even a maximum SPL of 126 dB.

Based on a very solid plywood enclosure with a scratch free, durable polyurethane black coating, the RX series are excellent for on the road.

Its multi-angled enclosure can be used arrayed, on a speaker stand, standing upright on the floor and also as a monitor. Embedded steel L-tracks provide convenient multi-axis suspension. Their very compact size and ergonomic grips make the RX easy to handle and transport.



RX115 rear



RX115 solid grip

# RX 115

## Speaker Cabinet

PROFESSIONAL SOUND EQUIPMENT

### PRODUCT FEATURES :

Drivers : HF MF	1.3" 15"
Dimensions (WxHxD)	465 x 378 x 720
Weight Net	25 kg
Connectors	Speakon ML4MPX2
Construction	Plywood
Fittings : Handles	1 (at the top)
Front finish	perforated steel grille
Flying points	6 double M10
Stand fittings	1
Colour	black

### SYSTEM SPECIFICATIONS :

RMS Power	300W
Max Power	600W
Impedance	8 Ohm
Sound pressure 1W/1m	101 db
Max Sound pressure	126 dB
Horizontal coverage	90°
Vertical coverage	75°
Frequency response -3 db	62 - 18.000 Hz
-10 db	50 - 20,000 Hz
Crossover freq.	2.000 Hz


### SYSTEM OPERATION:

Electronic controller	
-----------------------	--

### SHIPPING & ORDERING :

Packaging	carton box
Shipping weight and volume	29 kgr - 0.20 Cbm
Accessories	Protection bag Eye bolt

\* AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our products.



**AUDAC**  
www.audac.eu

For a period of 2 years, starting from the original date of purchase, Audac products are covered against defects in workmanship or materials. The defective item will be repaired or replaced at the option of Audac, with no charge for materials or labour. You have to adequately pack up and dispatch the item prepaid to an Audac authorized distributor/service centre. Unauthorized repair shall void the warranty. Cosmetics and finish are not covered by this Audac warranty. The warranty is also voided if, in Audac's opinion, the items have failed due to user abuse, accidents, modifications or any type of misuse.

