Subwoofer System





SX418

FEATURES :

Powerful sub system (129 db SPL MAX) 18" excursion driver

Sophisticated control electronics ensure reliable, linear operation

Integral 35 mm pole mount that supports 1 mid-high Loudspeaker

APPLICATIONS:

Indoor fixed installed PA for clubs, A/V, theater, broadcast, etc.

SX418

The AUDAC ® SX 418 is a top class powerful Tandem Ported Design subwoofer for indoor applications. Incorporating this subwoofer in any large room wouldn't be a problem, but in the open air it would be.

The results of the carefully designed and tuned subwoofer will satisfy most demands for high power, extreme low frequency performance at exceptionally low distortion levels.

Accurate bass does not always sound spectacular, it sounds real. A really good sub will integrate so seamlessly into your system that it will not draw attention to itself.

This single 18 inch subwoofer with a power of 700 Watt RMS and 100 dB SPL sensitivity is capable of a maximum SPL of 129 dB with an extremely flat frequency response between 35 - 250 Hz!

Its built-in head base makes it possible to combine with any top-cabinet of your choice.

The cabinet is constructed of 18 mm multi-ply hardwood and coated with scratch free, durable structure black paint.



SX418 grip

About Audac :

AUDAC provides a complete range of audio equipment such as amplifiers, loudspeakers, microphones, conference microphones and much more.



SX 418 subwoofer system


| PRODUCT FEATURES : | |
|--------------------|-------------------------------------|
| Drivers | 1x18" |
| Dimensions (BxHxD) | 540 x 730 x 750 mm |
| Weight | 54 kg |
| Connectors | ML4MPX2 |
| Construction | textured polyurethane black coating |
| Fittings : Handles | 2, integrated to cabinet |
| front finish | perforated steel grille |
| Flying points | none |
| Stand fittings | built-in stand fitting, 35mm |
| Colour | black |


SYSTEM SPECIFICATIONS :

| RMS Power | 700W |
|--------------------------|-------------|
| Max Power | 1400W |
| Impedance | 8 Ohm |
| Sound pressure 1W/1m | 100 dB |
| Max Sound pressure | 129 dB |
| Frequency response -3 db | 35 - 250 Hz |
| -10 db | 25- 250 Hz |

| on box |
|---------------|
| gr - 0.40 Cbm |
| |

* AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our products.





For a period of 2 years, starting from the original date of purchase, Audac products are covered against defects in workmanship or materials. The defective item will be repaired or replaced at the option of Audac, with no charge for materials or labour. You have to adequately pack up and dispatch the item prepaid to an Audac authorized distributor/service centre. Unauthorized repair shall void the warranty. Cosmetics and finish are not covered by this Audac warranty. The warranty is also voided if, in Audac's opinion, the items have failed due to user abuse, accidents, modifications or any type of misuse.

w w w a u d a c . b e

