

MCD2.2



:: Product Description

- * Twin CD/MP3-player for DJ's
- * Alphanumeric LCD display supports ID3V2 tags (song title, artist and bit rate)
- * Full MP3 Playback (max. 999 MP3-files / 255 Folders on 1 CD)
- * - MPEG1 layer3 (32 + 44,1 + 48kHz)
- * - MPEG2 layer3 (16 + 22,05 + 24kHz)
- * - MPEG2.5 layer3 (8 + 11,025 + 12kHz)
- * Supports both CBR and VBR bitrate modes.
- * Reads CD-DA, CD-R, CD-RW
- * Anti-shock Memory 20 seconds
- * Seamless loop (IN/OUT/RELOOP) + with stutter effect
- * Real-time loop edit function
- * Real-time cue ("Cue on the fly")
- * Instant start
- * Fader start/stop (back cue)
- * 1/75sec Frame search, also on MP3
- * Pitch ranges: +/-4% +/-8% +/-16%, also on MP3
- * Full automatic beat counters with extra TAP-function
- * Pitch bend on jog wheel for perfect mixes
- * Auto cue function (-48dB)
- * 4 different speed scan
- * Selectable elapsed, remain and total remain time display

- * Pitch display.
- * Single/continuous play
- * Folder mode: track search limited to one folder
- * Track mode: track search on the entire CD/CDROM
- * Relay play allows consecutive playback on two decks
- * S/PDIF digital output on RCA/cinch

:: Technical Information

- * Power Supply: AC 230V / 50Hz
- * Power Consumption: 26W
- * Output level: 2.0Vrms +/-1dB @ 1kHz,0dB
- * Frequency response: 20-20.000Hz (+/-1dB@0dB output)
- * THD + noise: 0.01% @ 1kHz, 0dB
- * S/N Ratio (IHF-A): >90dB @ 1kHz, 0dB (IHF-A weighted, w/20KHz LPF)
- * Short access time (next track):
- * Long access time (track 1  20):
- * Laser Pickup: Sony KSM-213CCM 3spot detection 780nm
- * Electronic tracking: Full automatic digital tracking.
- * DISC FORMAT:
- * Possible file extensions: .mp3 ~ .MP3 ~ .mP3 ~ .Mp3
- * ISO9660: max. 63 character style
- * Joliet: max. 63 character style
- * CD-ROM sector format: mode-1 only
- * Max. Folders: 255
- * Max. Files per Folder: 255
- * Max. Files: 999
- * MP3 FORMATS:
- * MPEG1 Layer3 (ISO/IEC11172-3): mono / stereo sampled at: 32 - 44,1 - 48kHz
- * Bitrates: 32 - 320 Kbps
- * Bitrate modes: CBR (Constant Bitrate) or VBR (Variable Bitrate)
- * MPEG2 Layer3 (ISO/IEC13818-3): mono / stereo sampled at: 16 - 22,05 - 24kHz
- * Bitrates: 32 - 160 Kbps
- * Bitrate modes: CBR (Constant Bitrate) or VBR (Variable Bitrate)
- * MPEG2,5 Layer3: mono / stereo sampled at: 8 - 11,025 - 12kHz
- * Bitrates: 32 - 160 Kbps
- * Bitrate modes: CBR (Constant Bitrate) or VBR (Variable Bitrate)
- * Dimensions: Main unit 482(W) x 88,8(H) x 262,5(D) mm
- * Control unit 482(W) x 88,8(H) x 94(D) mm
- * Weight: 6,6kg

:: Extra information and order codes
