

KA3-3

High technology self-powered PA System and line array element

PRELIMINARY

DATASHEET



Features:

- Very light weight
- Compact design
- Optical limiters
- Electronically protected
- Ultra-high efficiency
- DSP on-board to drive all K-array products
- Remote control
- eDSP management software
- Top quality components for outstanding performance Aluminum frame

Applications:

- Theatrical sound reinforcement
- Concert halls, clubs, houses of worship
- Exhibit audio for museum displays
- Cinema and installed AV systems
- Diffused sound systems

KA3-3	
Output power	
Max power 2Ω	4 x 150 w ^(EIAJ)
Max power 4Ω	4 x 75 w ^(EIAJ)
Max power 8Ω	4 x 40 w ^(EIAJ)
Connectors	4 x 2-pin screw connector
Protection	
Thermal protection	Yes
Short circuit / over-load	Yes
Clip limit, Analog signal limit	Yes
Audio Input	
Connectors	2 x Female 3-pin bal .XLR
Wiring	Pin1 = Ground / Pin2 = hot (+) / Pin3 = cold (-)
Remote control Input	
Connectors	2 x Female 8-pin RJ45 + USB
Remote control	
Protocol	RS485 - eDSP software
DC power	
Connectors	2-pin Phoenix screw connector
Operating range	20 - 48 Vdc
Power continuous and burst current	10A (>10) - 16A (<1)
Physical	
Dimensions	11 x 8.5 x 19.2 cm (4.33"x 3.5"x 7.56")
Weight	1.2 Kg (2.65 lbs)
<small>Notes for data New materials and design are introduced into existing products without previous notice. Present systems may differ in some respects from those presented in this brochure</small>	

www.k-array.com

HP Sound Equipment s.r.l. Viale Roma 7/i - 50037 - San Piero a Sieve (FI), Italy
tel. +39 055 8487222 - fax. +39 055 8487238 - e-mail: info@k-array.com