

# KU36

Ultra slim, high power  
sub woofer

PRELIMINARY

DATASHEET



## Features:

- Unique performance-to-size ratio
- 6" long-excursion woofer
- Double 6" passive radiator
- Extended frequency response
- Electronically protected
- Integrated flying points
- Double voice coil ( $4\Omega+4\Omega$ )
- Top quality components for outstanding performance
- Weather proof, suitable for outdoor installations
- Available in black or white

## Applications:

- Theatre, Club, Churches
- To extend the low range in small and midium rooms
- Portable and installed AV systems
- Stage and AV studio monitoring

Power handling

Impedance

Operating frequency range

SPL 1W / 1mt

Maximum SPL

Full range

Connectors

Wiring

Dimensions

Weight

## KU36

### Acoustics

2 X 80 W <sup>(AES)</sup>

2 X  $4\Omega$

45 Hz - 300 KHz.

89 dB

115 dB continuous - 121 dB peak

### Transducers

6" Neodymium magnet with 1.5" voice coil

### Audio Input

4-pin Phoenix

Pin1=Ch 1-, Pin2=Ch 1+, Pin3=Ch 2-, Pin4=Ch 2+

### Recommended Amplifiers

KA1-1, KA3-3, KA7-7, KA10-10

### Physical

50.7 x 17.5 x 10.5 cm (19.96" x 6.89" x 4.13")

6.8 Kg (15 lbs)

New materials and design are introduced into existing products without previous notice. Present systems may differ in some respects from those presented in this brochure.

[www.k-array.com](http://www.k-array.com)

HP Sound Equipment s.r.l. Viale Roma 7/i - 50037 - San Piero a Sieve (FI), Italy  
tel. +39 055 8487222 - fax. +39 055 8487238 - e-mail: [info@k-array.com](mailto:info@k-array.com)