

MPX-4PA



Number: 20.2070

3-zone mixer

- 3 zones with routing facility of all input channels as desired
- XLR and RCA zone outputs
- 6 input channels (4 stereo ways, 2 microphone ways)
- Both microphone ways can only be routed together
- Recessed gain control for each input channel
- Microphone ways with 2-way tone control, talkover and PAD switches
- Switchable stereo channels: 2 x phono/line and 2 x line/line
- Zone outputs, each with 3-way equalizer, LED level display of the stereo master, balance control, pre-fader listening (PFL) and mono/stereo selector switch
- Adjustable headphone output with pre-fader listening (PFL) to the stereo input channels and the zone outputs
- Connection for gooseneck light GNL-200, GNL-204 or GNL-205

Technical Facts Mixers

Mic input

1.5mV

Phono input

3mV

CD input

150mV

Line input

150mV

Master output

1V/600Ω

Record output

-

Headphones

≥ 8Ω

Frequency range

20-20,000Hz

THD

0.1%

S/N ratio

61dB, unweighted

Equalizer, bass

+12dB, -12dB/50Hz

Equalizer, midrange

+12dB, -12dB/1kHz

Equalizer, treble

+12dB, -12dB/10kHz

Talkover

-16dB

Gooseneck light

12V/5W, BNC

Power supply

230V~/50Hz/20VA

Admiss. ambient temp.

0-40 °C

Dimensions

482x177x105mm, 4RS

Weight

3.75kg

KWW500R7150122-128