

EW766 DLP® Projector

Versatile Widescreen Installation...



Widescreen presentations and HD entertainment

Bright projection – 4000 ANSI Lumens

Digital and Analogue connectivity includes: HDMI, DVI-D, dual VGA

Low ownership costs – up to 4000hrs lamp life

Networking - RJ45 control and monitoring

Environmentally friendly design <1W standby mode

DLP® filter-free design – Virtually no maintenance



Powerful installation projector

Widescreen, HD Ready. The high performance EW766 with a brightness of 4000 ANSI Lumens is ideally partnered with a widescreen notebook and HD sources to deliver bright widescreen images from a great distance.


The introduction of PureShift technology gives your projector outstanding flexibility and with a 1.5x zoom makes the EW766 an ideal replacement for existing ceiling mounted systems.


The environmentally friendly EW766 has energy saving features including <1W standby mode and auto power off saving you both time and money. Long lamp-life of 4000hrs combined with our unique Optoma Colour and Imager guarantees ensure hassle-free, long-lasting projection.

1.5X ZOOM AND PURESHIFT - EASY INSTALLATION

The EW766 can project a 100" diagonal image from any distance between 3.4m and 5.2m. The PureShift system provides a lens shift function that can be used to adjust the position of the projected image either horizontally or vertically within the range detailed in the diagrams below.

When replacing existing projectors, the 1.5x zoom and PureShift system will greatly increase your installation flexibility.





Above diagrams for guide purposes only

TRUE WXGA RESOLUTION

The EW766 is the perfect companion for widescreen laptops. Your presentations will appear as sharp and detailed as they do on your widescreen laptop in WXGA (1280 x 800). WXGA resolution gives 30% more pixels than XGA.






WXGA

PROJECTOR CONTROL AND MANAGEMENT

Projectors can be controlled and monitored over a network (LAN) using a web browser.

- Manage up to 99 projectors at the same time (via master PC)
- Control and alter the projector settings using a simple web browser page
- Instant onscreen display of messages to projectors
- Set up email alerts for warning messages
- Ideal for large installations both in the educational and business environments



CONTROL

The extensive RS232 command structure makes it simple and easy to control the EW766 with any control system.



AMX Compatibility – Dynamic Discovery Protocol is incorporated into the EW766. This feature allows for easy installation with AMX control systems.

EXTENSIVE CONNECTIVITY

This native WXGA projector accepts a wide variety of computer and video input signals. Connectivity includes: HDMI, dual VGA–SCART and Component, S-Video, Composite, RS232 and RJ45.

Three audio inputs for individual PC and video connections enable the EW766 to function as an audio switcher and volume controller, thereby eliminating complicated and costly additional audio hardware and cabling.



CLEAR, FOCUSED IMAGES

Technology from Texas Instruments produces a stunning 2500:1 contrast ratio for pin sharp graphics and crystal clear text. Crisper whites, ultra-rich blacks make images come alive and text easier to read - ideal for business and education presentations.



500:1 contrast ratio

2500:1 contrast ratio

‡Simulated Image

AMAZING COLOURS

The EW766 incorporates BrilliantColor™ technology to produce stunningly bright images with perfectly balanced life-like colours.



COLOUR AND IMAGE PERFORMANCE

Optoma guarantees colour quality will remain as new for 5 years*

Once you've purchased the EW766, Optoma guarantees that the colours will not fade and the image performance will not degrade for a minimum of 5 years.







MAINTENANCE FREE = LOWER TOTAL COST OF OWNERSHIP (TCO)

DLP® technology ensures lower cost of ownership, longer life and improved reliability compared to other technologies.

The filter-free projector design means no more regular filter cleaning or replacements, saving you time and money.



ENVIRONMENTALLY FRIENDLY

The EW766 incorporates energy saving features to reduce power consumption and extend the lamp life.

The timer control functions can automatically switch the projector off to standby mode <1W, conserving power and extending the lamp life to an astonishing 4000hrs**.

FEATURES

- Preset display modes
- Easy to use remote with laser pointer, mouse control and direct source selection
- Direct power on and Auto power off
- Customised start-up logo

EW766 SPECIFICATIONS

Brightness - BRIGHT mode	4000 ANSI Lumens				
Contrast	2500:1				
Native Resolution	WXGA 1280 x 800				
Compressed Resolution	UXGA (1600 x 1200)				
Noise Level	28dB				
Keystone Correction	± 40° Vertical				
PureShift Movement	+25% Vertical, ±30% Horizontal (Max Movement)				
Tarocinit movement	Before installation please read EW766 install guide				
Projection Lens	F/2.45 ~ 2.9; f=22.18 ~ 33.27mm, 1.5x Manual Zoom				
Throw Ratio	1.57 - 2.39:1 (Projection Distance:Image Width)				
Projection Distance	1.2 - 10m				
Image Size	0.59 – 7.51m (23.32" - 295.71") Diagonal 16:10				
Display Technology	Single 0.65" WXGA DMD chip DLP® Technology				
Display Technology	by Texas Instruments				
Aspect Ratio	16:10 Native, 16:9, 4:3 Compatible				
Lamp Life**	4000/3000 (STD/BRIGHT mode)				
Weight	4.6 kg				
Dimensions (W x D x H)	364 x 283 x 127 mm				
Remote Control	Full function remote with mouse control, laser pointer				
INDUITO.	and direct source selecting				
INPUTS	HDMI (HDCP) - audio supported				
	DVI-D (HDCP)				
	2 x 15 Pin D-Sub VGA (SCART & Component via adaptor)				
	S-Video 4 Pin Mini Din				
	Composite RCA				
	3 x 3.5mm Audio Mini Jack				
	USB (remote mouse)				
CONTROL	RS232 - 3 Pin D-sub & RJ45 - Network Control				
OUTPUT	15 Pin D-Sub VGA (monitor loop-through)				
	3.5mm Audio Mini Jack				
	+12v Trigger				
Audio	4W Speaker				
On Screen Display	18 Languages: English, German, French, Italian, Spanish,				
	Portuguese, Polish, Dutch, Russian, Finnish, Swedish,				
	Greek, Norwegian, Danish, Hungarian, Czech,				
	Turkish & Arabic				
Video Compatibility	PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i/1080p				
Uniformity	85%				
Displayable Colours	134.2 Million				
Horizontal Scan Rate	15 - 91.1kHz				
Vertical Scan Rate	50 - 85Hz				
Power Supply	100 - 240V, 50 - 60Hz				
Power Consumption	233W BRIGHT mode < 1W Standby mode				
1 ower consumption	207W STD mode < 1W Standby mode				
Operating Conditions	Operating: 5 - 40°C, 85% Humidity (Max),				
operating continuous					
Conwity	3000m Altitude (Max)				
Security Standard Accessories	Kensington Lock Port, Password Protection Lens Cover, AC Power Cord, VGA Cable, RS232 Cable,				
Stanuaru Accessories	USB Cable, Full Function Remote, Batteries x 2, Quick				
D.110	Start Guide, CD User Manual, Warranty Card, WEEE Card				
RoHS	Compliant				
Lamp Warranty	6 months or 1000 hours - whichever comes sooner				
Warranty	Warranty may vary by country. Please see				
	www.optomaeurope.com or ask your local				
	supplier for details				
Colour Guarantee*	5 Years				
Imager Guarantee***	5 Years				

EASY TO USE REMOTE CONTROL


EW766 Remote Control

- 1 Laser
- 2 Remote Mouse
- 3 Page Up/Down Control
- 4 Help/Enter
- 5 Vertical Keystone Correction
- 6 Volume Control
- 7 AV Mute
- 8 Digital Zoom Control
- 9 Direct Input Source Selection

EW766 Connections

- 10 USB (Remote Mouse)
- 11 HDMI (audio supported)
- **12** DVI-D
- 13 VGA 1 SCART & Component
- **14** VGA 2
- 15 VGA Out
- 16 S-Video
- 17 Composite Video
- 18 RS232 3 Pin
- **19** RJ45
- 20 Audio In (DVI-D)
- 21 Audio In (VGA 1 & 2)
- 22 Audio Out
- 23 Audio In L&R (S-Video & Composite)
- 24 +12v Trigger
- 25 Kensington™ Lock

Exceptional Connectivity / Multiple Terminals



Easy to use remote with buttons to change the input sources



Projection Distance (m)	Max. Horizontal Image Size (m)	Min. Horizontal Image Size (m)	Max. Screen Height (m)	Min. Screen Height (m)	Max Diagonal Image Size (m)	Min Diagonal Image Size (inch)	Max Diagonal Image Size (inch)
1.20	0.76	0.50	0.48	0.31	0.90	23.31	35.49
2.00	1.27	0.84	0.80	0.52	1.50	38.85	59.14
2.50	1.59	1.05	1.00	0.65	1.88	48.56	73.93
3.00	1.91	1.26	1.19	0.78	2.25	58.28	88.71
4.00	2.55	1.67	1.59	1.05	3.00	77.70	118.29
5.00	3.18	2.09	1.99	1.31	3.76	97.13	147.86
6.00	3.82	2.51	2.39	1.57	4.51	116.55	177.43
7.00	4.46	2.93	2.79	1.83	5.26	135.98	207.00
8.00	5.10	3.35	3.18	2.09	6.01	155.40	236.57
9.00	5.73	3.77	3.58	2.35	6.76	174.83	266.14
10.00	6.37	4.18	3.98	2.62	7.51	194.26	295.71

For guide purposes only

EW766 is also capable of 16:9 & 4:3 aspect ratio projection. When projecting a 16:9 & 4:3 image the image sizes, screen height and offset information will differ from the above.

Optoma Europe Ltd.

42 Caxton Way, Watford Business Park, Watford, Hertfordshire, UK. WD18 8QZ





