



## Digit 3K6





## :: Product Description

- \* A real breakthrough in professional amplifier technology: Synq introduces a new range of CLASS-D AMPLIFIERS with exceptional power and competitive pricing!
- \* The extremely high efficiency, reduced power waste and very low heat dissipation are the main advantages of these PWM-amplifiers!
  - \* Incredible space savings for mobile applications: enclosure only 1unit high!
  - \* Incredible low weight: only 5,6kg!
  - \* Extremely high power output: 2x 1800Wrms @ 4ohms!
  - \* Output in bridge mode: 3600Wrms @ 8ohms
  - \* All the protections you can think of for professional use:
    - \* Signal + current limiters
    - \* Overload protection
    - \* Short circuit current protection
    - \* DC protection
    - \* Thermal protection
    - \* AC, VHF protection
    - \* Soft start
    - \*
  - \* Very powerful bass response, also perfect for subwoofers!
  - \* Switchable 30Hz HPF (high pass filter) eliminates unwanted, power consuming, subsonic frequencies.
  - \* 3 different working modes: stereo, bridge mode, mono mode (inputs linked)





- \* Balanced in/outputs on XLR + 6.3mm jack
- \* 2 Speakon connectors (left and right outputs)
- \* 1 separate Speakon output for bridge mode

## :: Technical Information

Power - stereo (or mono): 2x 1050Wrms @ 8 ohms Power - stereo (or mono): 2x 1800Wrms @ 4 ohms

Power - bridge: 1x 3600Wrms @ 8 ohms Frequency response: 5 - 36.000Hz +/-1dB

THD: Input sensitivity: 1000mV Input impedance: 20k balanced Input impedance: 10k unbalanced

S/N ration: >100dB

Crosstalk (8ohm/1kHz): 90dB Damping Factor (8ohm/1kHz): >300

Slew Rate: 29V/uS Weight: 5,6kg

Dimensions: 482x301x44mm (19"/1U)